VANCLEAVE SCHOOLS HVAC UPGRADES JACKSON COUNTY SCHOOL DISTRICT

12602 HWY 57, 4725 BULLDOG LN & 12424 HWY 57 VANCLEAVE, MISSISSIPPI 39565


LOWER ELEMENTARY, MIDDLE & HIGH SCHOOLS

FEBRUARY 03, 2023 REV 0 - ISSUED FOR CONSTRUCTION




David J. Machado, PE Brad P. Patano, PE Gerrod W. Kilpatrick, PE Bradford A. Jones, AIA Fernanda A. Silva, AIA





	ABBREVIA	TIONS INDEX	
A	E (CONT)	L	R (CONT)
& AND @ AT Ø ANGLE A/C AIR CONDITIONING ACT ACOUSTICAL CEILING TILE ADDT'L ADDITIONAL ADJ ADJUSTABLE AF ACCESS FLOORING AFD AUTOMATIC FIRE DAMPER AFF ABOVE FINISH FLOOR ALUM ALUMINUM	EJEXPANSION JOINTELECELECTRICALEL/ELEVELEVATIONEMBEDEMBEDDEDENGRENGINEERENTENTERING/ ENTRYEQEQUALEQUIPEQUIPMENTESEXPOSED STRUCTUREEXHEXPANSIONEXPANEXPANSION	LAM LAMINATE LAV LAVATORY LT LIGHT MA MIXED AIR MAS MASONRY MAT'L MATERIAL MAX MAXIMUM	RET RETURN RM ROOM R.O ROUGH OPENING RTU ROOF TOP UNIT SA SUPPLY AIR SAN SANITARY
ALT ALTERNATE APPROX APPROXIMATE ARCH ARCHITECT ASF ALUMINUM STORE FRONT BTWN BETWEEN BIT BITUMEN	EXT EXTERIOR FA FIRE ALARM FAC FIRE ALARM CABINET FD FLOOR DRAIN FAR FIRE ALARM REMOTE FE FIRE EXTINGUISHER	MECH MECHANICAL MFR/MFGR MANUFACTURER MIN MINIMUM MISC MISCELLANEOUS MO MASONRY OPENING MAS MODIFIED MRV MOISTURE RELEASE VENT MT METAL THRESHOLD MTD MOUNTED	SAFM SELF ADHERING FLASHING MEMBRANE SCHED SCHEDULE SCWD SOLID CORE WOOD SECT SECTION SF STOREFRONT/ SQUARE FEET SHT SHEET SIM SIMILAR SL SLOPE
BITBITOMENBJBAR JOISTBLDGBUILDINGBLKBLOCKBLK'GBLOCKINGBLTBUILTBMBEAMBOBOTTOM OFBRBACKER RODBTWNBETWEEN	FE FIRE EXTINGUISHER FEC FIRE EXTINGUISHER CABINET FH FH FIRE HYDRANT FIN FINISH FLR FLOOR FOC FACE OF CONC FOB FACE OF BRICK FR FRAME FS FLOW SWITCH — FTG	MTD MOUNTED MTL METAL N/A NOT APPLICABLE NF NATURAL FINISH NIC NOT IN CONTRACT NO / # NUMBER NOM NOMINAL	SL SLOPE SP SPACING SPEC SPECIFIED/ SPECIFICATIONS SQ SQUARE SS STAINLESS STEEL STD STANDARD STL STEEL STRUCT STRUCTURAL SUP SUPPLY SUSP SUSPENDED
CAP CAPACITY C/C CENTER TO CENTER CCTV CLOSED CIRCUIT	GA GAUGE GALV GALVANIZED	NTS NOT TO SCALE	T&B TOP & BOTTOM
TELEVISION CJ CONTROL JOINT CL CLEAR CLG CEILING CLO CLOSET CLR COLOR CMU CONCRETE MASONRY UNIT CONTR CONTR CONTRACTOR COL COLUMN COMP COMPRESSION OR	GC GENERAL CONTRACTOR GF CMU GROUND FACE CMU GL GLASS GPM GALLONS PER MIN. GYP BD GYPSUM BOARD HB HOSE BIB HC HANDICAP	OA OUTSIDE AIR OC ON CENTER OCEW ON CENTER EACH WAY OH OVERHEAD OPN'G OPENING OPP OPPOSITE OZ OUNCE P	TBMTEMPORARY BENCH MARKTELTELEPHONET>OUNGE & GROOVETHRESHTHRESHOLDTLTTOILETT.O.TOP OFT.O.B.TOP OF BEAMT.O.S.TOP OF STRUCTURETPTOILET PAPER HOLDERTRTDTREATEDTYPTYPICAL ALL SIMILAR
COMPRESSED CONC CONCRETE COND CONDENSATE CONST CONSTRUCTION CONT CONTINUOUS CPLNG COUPLING CPT CARPET CT CERAMIC TILE CTB CERAMIC TILE BASE CTR CENTERS CENTER CW COLD WATER	HDWR HARDWARE HM HOLLOW METAL HP HIGH POINT HORIZ HORIZONTAL HR HOUR HT HEIGHT HW HOT WATER HVAC HEATING, VENTILATION, AIR CONDITIONING	± , +/_PLUS OR MINUSPTPAINTPART'NPARTITIONPRE-FINPRE FINISH(ED)PLPLATEPPLPROPERTY LINEPLAMPLASTIC LAMINATEPLYWDPLYWOODPNLPANELPPPOWER POLEPRPAIR	UC UNDER COUNTER UL UNDERWRITER'S LABORATORY UNO UNLESS NOTED OTHERWISE
DIA / DIAMETER DB DRY BULB DBL DOUBLE DEFL DEFLECTION DEPT DEPARTMENT	IC INTERCOM INSUL INSULATION INT INTERIOR INV INVERT	PRE FAB PREFABRICATED PROJ PROJECTION PSF POUNDS/SQUARE INCH PTD PAPER TOWEL DISPENSER Q	VAR VARIES VD VOLUME DAMPER VERT VERTICAL VCT VINYL COMPOSITION TILE VIF VERIFY IN FIELD VTR VENT-THRU-ROOF VWC VINYL WALL COVERING
DET/DTL DETAIL DISP DISPENSER DK DARK	JAN JANITOR JNT JOINT	QT QUARRY TILE GTB QUARRY TILE BASE GTY QUANTITY	W
DN DOWN DP DAMP PROOFING DS DOWNSPOUT DWG(S) DRAWING(S) EA EACH EDF ELECTRONIC DRINKING FOUNTAIN EF EXHAUST FAN EFC EACH FACE	LAM LAMINATE(D) LAT LAY-IN ACOUSTICAL CEILING LAV LAVATORY LF LINEAR FEET LG LEG LP LIGHT POLE	RA RETURN AIR RB RUBBER BASE RD ROOF DRAIN RE: REFER TO REF REFERENCE REFR REFRIGERATOR REINF REINFORCED REQ'D REQUIRED	W WIDE, WIDTH W/ WITH W/O WITHOUT WD WOOD WG WATER GAUGE WGVP WIRE GLASS VISION PANEL WH WATER HEATER WP WATERPROOFING WPMB WATERPROOFING MEMBRANE



PROJECT MAP A the second second is a VANCLEAVE LOWER ELEMENTARY SCHOOL 12602 MS-57, VANCLEAVE, MS 39565 VANCLEAVE HIGH SCHOOL 12424 MS-57, VANCLEAVE, MS 39565 BALLPARK RD VANCLEAVE MIDDLE SCHOOL 725 BULLDOG LN, VANCLEAVE, MS 39565 VICINITY MAP JACKSON COUNTY SCHOOL DISTRICT 4700 COLONEL VICKREY RD VANCLEAVE, MS 39565

MATERIAL HATCH LEGEND


Ste	el
Stu	CCO
- - - -	
Sa	nd
Wc	od 02
	-

Gyp	sum	-Pla	aster				
Plas	tic						
\mathbf{v}		\mathbf{v}		\mathbf{v}		\mathbf{v}	
	\forall		\mathbf{v}		\checkmark		\checkmark
\forall		\forall		\forall		$\mathbf{\Psi}$	
	\forall		\forall		\checkmark		\forall
Site	Gra	ISS					
_					_	_	
		~	_	\geq	_		\geq
			~	_	\leq	_	>
		-	~				
	\leq			-	_	\sim	


DRAWING INDEX

GENERAL INDEX PLUMBING INDEX C000 COVER SHEET G101 GENERAL NOTES, ABBREV, SYMBOLS, SHEET INDEX MECHANICAL INDEX CIVIL INDEX N/A STRUCTURAL INDEX S100 LOWER ELEMENTARY SCHOOL – MECHANICAL EQUIPMENT PAD PLAN, SECTIONS, & DETIALS S101 HIGH SCHOOL – COOLING TOWER FOUNDATION PLANS, SECTIONS, & DETAILS MH103 HIGH SCHOOL MECHANICAL HVAC PLAN ARCHITECTURAL INDEX

- M001 MECHANICAL SYMBOLS & ABBREVIATIONS
- M002 MECHANICAL NOTES
- MS101 LOWER ELEMENTARY SCHOOL MECHANICAL SITE PLAN
- MS102 MIDDLE SCHOOL MECHANICAL SITE PLAN MS103 HIGH SCHOOL MECHANICAL SITE PLAN
- MH101 LOWER ELEMENTARY SCHOOL MECHANICAL HVAC PLAN
- MH102 MIDDLE SCHOOL MECHANICAL HVAC PLAN
- MH501 MECHANICAL HVAC DETAILS
- MH601 MECHANICAL HVAC SCHEDULES



 ARC 9 1 	18 Ho Biloxi, P: ww.n Davic	signe signe Missi 228. npde J. M d P. F d W. ord A	d A d A ssip 388. sigr ach ach Cata Kilp	NGI DBU VeS pi3 195 ngro nad ino, atrico	NEE ild" uite 953 0 0 0 0 0 PE ck, F	RIN e F 0 .Us E PE A								
	Fernanda A. Silva													
VANCLEAVE SCHOOLS HVAC UPGRADES				JACKSON COUNTY SCHOOL DISTRICT										
SCAL PROJ DRAV CHEC	.E: AS IECT N VN BY CKED	<u>INDIC</u> NO:01 ': BY:F/	CATE 55.2 AS	<u>=D</u> 2.00 MA)7 J,									
GENERAL NOTES, ABBREV,	SYMBOLS, SHEET INDEX													
DATE REVISION / SUBMITTAL	02.03.23 ISSUED FOR CONSTRUCTION													
NO.														
	C	1)-										
BAR		RIFY				win	IG							



REINFORCING STEEL

- 1. ARRANGEMENT AND BENDING OF REINFORCING STEEL SHALL BE IN ACCORDANCE WITH THE ACI DETAILING MANUAL, LATEST EDITION.
- 2. DETAILING OF REINFORCING STEEL SHALL CONFORM TO THE ACI MANUAL OF PRACTICE FOR DETAILING REINFORCED CONCRETE STRUCTURES, ACI 315. REINFORCEMENT SHALL NOT BE WELDED UNLESS NOTED OR APPROVED BY THE ENGINEER.
- 3. REINFORCING STEEL SHALL BE NEW AND ALL BARS BE DEFORMED. REINFORCEMENT STEEL SHALL BE STORED IN SUCH MANNER TO PREVENT EXPOSURE TO THE ELEMENTS AND SHALL BE FREE OF RUST BEFORE PLACEMENT.
- 4. REINFORCING BARS: ASTM A615 GRADE 60 ASTM A706 GRADE 60 FOR WELDABLE REINFORCING
- 5. BAR LAPS SHALL BE CLASS B TENSION LAPS (U.N.O.) AND SHALL BE LAPPED WITH MINIMUM LENGTHS AS SHOWN IN TYPICAL DETAILS, WHERE SPLICES ARE REQUIRED IN REINFORCING. SHORTER LAPS MAY BE ACCEPTABLE IF SPECIFIC LOCATIONS OF ALTERNATE LAPS ARE SHOWN ON THE REINFORCEMENT PLACEMENT DRAWINGS, WITH CALCULATIONS SUBMITTED/STAMPED BY PROFESSIONAL ENGINEER REGISTERED AND LICENSED IN THE STATE OF PROJECT LOCATION, JUSTIFYING THE ALTERNATE LAP LENGTHS.
- 6. PROVIDE SUITABLE CHAIRS, TIES, WIRE SPACERS, ETC. FOR SUPPORTING REINFORCING STEEL IN PROPER LOCATION WHILE PLACING CONCRETE. "WET STICKING" DOWELS WILL NOT BE PERMITTED.
- 7. WELDED WIRE MATERIAL SHALL COMPLY WITH AMERICAN SOCIETY OF TESTING MATERIALS (ASTM) A185 STANDARD SPECIFICATIONS. SUPPORT WELDED WIRE MATERIAL AT THE PROPER DEPTH PRIOR TO PLACING CONCRETE WITH MINIMUM CLEARANCES AS NOTED BELOW AND WITH APPURTENANCES NOTED BELOW. WELDED WIRE MATERIAL SHALL BE LAPPED ONE FULL MESH PANEL PLUS TWO (2) INCHES AT SIDES AND ENDS AND WIRED TOGETHER. LAP ALL SIDES AND ENDS EIGHT (8) INCHES, MINIMUM.
- 8. MINIMUM CONCRETE PROTECTIVE COVERING FOR REINFORCEMENT IN SURFACES NOT EXPOSED DIRECTLY TO THE GROUND SHALL BE: – 3/4" FOR SLABS, JOISTS, AND WALLS - 1 1/2" FOR BEAM STIRRUPS AND COLUMN TIES/SPIRALS.
- "WET STICKING" DOWELS WILL NOT BE PERMITTED.
- 9. MINIMUM CONCRETE PROTECTIVE COVERING FOR REINFORCEMENT IN SURFACES EXPOSED TO WEATHER OR IN CONTACT WITH GROUND SHALL BE:
 - -11/2" FOR BARS #5 OR SMALLER (U.N.O.) - 2" FOR BARS GREATER THAN #5 (U.N.O)
 - PROVIDE 3" COVER FOR CONCRETE CAST AGAINST & PERMANENTLY EXPOSED TO EARTH (U.N.O.).
- 10. CORNER BARS SHALL BE PROVIDED FOR ALL HORIZONTAL REINFORCING BARS AT INTERSECTIONS AND AND CORNERS OF ALL STRIP FOOTINGS, BEAMS, AND WALLS (U.N.O.). CORNER BARS SHALL BE OF THE SAME SIZE AND GRADE AS THE HORIZONTAL REINFORCING THEY CONNECT. MINIMUM LAP LENGTHS SHALL BE AS INDICATED AS INDICATED ON PLANS (U.N.O.).
- 11. REINFORCING STEEL SHOWN IN SECTIONS AND DETAILS ARE SCHEMATIC AND INDICATE THAT REINFORCEMENT IS PRESENT. SEE SCHEDULES, SECTIONS NOTES, AND GENERAL NOTES FOR ACTUAL REINFORCING REQUIRED.
- 12. REINFORCING STEEL SHALL BE PLACED IN ACCORDANCE (IAW) CRSI "PLACING REINFORCING BARS", LATEST EDITION.
- 13. PROVIDE ONE (1) #4 HOOP WITH 8" LAP IN SLAB AROUND ALL FLOOR DRAINS.

CAST IN PLACE CONCRETE

- 1. CONCRETE MIX DESIGN SHALL BE 3500 PSI IN 28 DAYS.
- 2. CONTRACTOR SHALL VERIFY ALL IN SLAB FIXTURE DIMENSIONS WITH ARCHITECTURAL, MECHANICAL, PLUMBING AND ELECTRICAL PLANS. ALL SLOTS, SLEEVES AND OTHER EMBEDDED ITEMS SHALL BE SET BEFORE CONCRETE IS PLACED. ALL FOUNDATION PENETRATIONS SHALL BE THROUGH THICKENED SLAB EDGE OR 6" CLEAR BELOW FOOTING. CONDUIT SHALL NOT BE PLACED WITHIN THE SLAB ON GRADE. CONDUIT SHALL BE INSTALLED BELOW THE SLAB ON GRADE. PIPES, CONDUIT, AND DUCTS SHALL NOT EXCEED ONE-THIRD THE SLAB THICKNESS (BASED ON THE MAXIMUM OUTSIDE DIAMETER) AND SHALL HAVE A CENTER-TO-CENTER SPACING OF NO LESS THAN (3) DIAMETERS, UNLESS SPECIFICALLY DETAILED. REGARDLESS OF DIAMETER, THE MINIMUM CLEAR SPACING BETWEEN CONDUITS SHALL BE 1 NO MORE THAN FOUR CONDUITS MAY BE PLACED ADJACENT TO EACH OTHER WITHOUT PRIOR APPROVAL FROM THE STRUCTURAL ENGINEER OF RECORD. PROVIDE 1" MINIMUM CLEARANCE FROM REINFORCEMENT. LOCATIONS AND SIZES OF OPENINGS, SLEEVES, ETC. REQUIRED FOR OTHER TRADES MUST BE VERIFIED BY THOSE TRADES PRIOR TO PLACING CONCRETE. SEE MECHANICAL AND ELECTRICAL DRAWINGS FOR LOCATION OF SLEEVES, ACCESSORIES, ETC.
- 3. NO ALUMINUM CONDUITS, FIXTURES, ETC. MAY BE IN DIRECT CONTACT WITH THE CONCRETE.
- 4. ALL HONEY-COMBING, SPALLS, CRACKS, ETC. SHALL BE REPAIRED. EXTENT OF DEFECTIVE AREA SHALL BE DETERMINED BY THE STRUCTURAL ENGINEER.
- 5. CHAMFER ALL EXPOSED EXTERNAL CORNERS OF CONCRETE WITH A $\frac{3}{4}$ " DEGREE CHAMFER, UNLESS NOTED OTHERWISE.
- 6. REFER TO PLANS FOR CONTROL JOINT LOCATIONS. CONSTRUCTION JOINTS MAY BE ADDED AS REQUIRED TO PREVENT THE FORMATION OF CONCRETE COLD JOINTS DURING PLACEMENT OF CONCRETE. CONSTRUCTION JOINTS SHALL BE INSTALLED IN LOCATIONS WHERE THE CONCRETE PLACEMENT OPERATION IS SCHEDULED FOR SEVERAL SEPARATE PLACEMENTS OR WHEREVER THE CONCRETE PLACEMENT IS DELAYED A SUFFICIENT AMOUNT OF TIME TO FORM A CONCRETE COLD JOINT.
- 7. SLABS ON GRADE SHALL BE A THICKNESS AND REINFORCING AS SHOWN ON PLANS. REINFORCING AS SHOWN ON PLANS AND SHALL BE HELD SECURELY FROM THE GROUND USING REBAR CHAIRS OR OTHER APPROVED METHODS (CUT CONCRETE BRICK MAY BE USED) TO ENSURE MESH STAYS AT DEPTH INTENDED.
- 8. UNDER NO CIRCUMSTANCES WILL DIGGING, TUNNELING OR TRENCHING BE ALLOWED AT OR NEAR ANY CONCRETE STRUCTURE WHICH MIGHT ACT TO UNDERMINE THE STRUCTURE.
- 9. EXPANSION JOINT FILLER SHALL BE PREMOLDED MATERIAL COMPOSED OF FIBERBOARD IMPREGNATED WITH ASPHALT CONFORMING TO ASTM D1751.
- 10. ALL DETAILS SHOWN ARE TYPICAL, SIMILAR DETAILS APPLY TO SIMILAR CONDITIONS.

STRUCTURAL STEEL

- 1. UNLESS SPECIFICALLY NOTED OTHERWISE IN PLANS, FABRICATION AND ERECTION OF STRUCTURAL STEEL SHALL BE IN ACCORDANCE WITH AISC SPECIFICATIONS, LATEST EDITION.
- 2. THE FABRICATOR SHALL BE RESPONSIBLE FOR THE DESIGN AND ADEQUACY OF ALL CONNECTIONS THAT ARE NOT DESIGNED OR FULLY DETAILED IN THE CONTRACT DOCUMENTS.
- 3. WHERE FIELD AND SHOP WELDS ARE INDICATED ON THE DRAWINGS, THEY SHALL BE THE SIZE AND TYPE NOTED. ALL WELDING OF STRUCTURAL STEEL SHALL BE DONE IN ACCORDANCE WITH THE LATEST EDITION OF AWS D1.1 CORRESPONDING TO THE AISC SPECIFICATION USED AND ALL WELDS INCLUDING FIELD WELDS SHALL BE MADE BY CERTIFIED WELDERS USING E70XX ELECTRODES.
- 4. THE CONTRACTOR SHALL PROVIDE ALL TEMPORARY BRACING REQUIRED TO MAINTAIN STABILITY UNTIL THE SYSTEM IS COMPLETE IN PLACE.
- 5. EXTERIOR EXPOSED STRUCTURAL STEEL PREP AND COATING SYSTEM: A. ALL STEEL AND FASTENERS SHALL BE HOT DIP GALVANIZED AFTER FABRICATION.
- 6. THE GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR INCLUDING THE COSTS FOR ALL MISCELLANEOUS STEEL IN THEIR BID REGARDLESS OF WHETHER OR NOT THOSE ITEMS ARE INDICTED ON THE STRUCTURAL DRAWINGS. THESE COSTS SHALL INCLUDE, BUT NOT LIMITED TO, MISCELLANEOUS STEEL ITEMS SHOWN ON ARCHITECTURAL, CIVIL, MECHANICAL, PLUMBING, AND ELECTRICAL DRAWINGS.
- 7. FIELD CUTTING, DRILLING, AND OTHER MODIFICATIONS OF STRUCTURAL STEEL COMPONENTS IS NOT PERMITTED WITHOUT WRITTEN APPROVAL OF THE STRUCTURAL ENGINEER OF RECORD. WHERE BEAM PENETRATIONS CANNOT BE AVOIDED OR WHERE CUTTING IS REQUIRED, THE CONTRACTOR SHALL SUBMIT, TO THE STRUCTURAL ENGINEER OF RECORD, ALL PERTINENT INFORMATION INCLUDING PENETRATION SHAPE, SIZE, LOCATION, AND METHOD OF CUTTING THE OPENING.


- AMERICAN IRON AND STEEL INSTITUTE (SPECIFICATIONS FOR THE DESIGN OF COLD FORMED STEEL

TF	Fy = 55,000 PSI (ASTM F1554) (HOT DIP GALVANIZED) Fy = 36,000 PSI (ASTM A36)
D CONC.	F'c = 3500 PSI IN 28 DAYS F'c = 3500 PSI IN 28 DAYS
RIC URAL BOLTS	Fy = 60,000 PSI (ASTM A615, GRADE 60) (ASTM A616 (S1), GRADE 60) ASTM A185 (FLAT SHEETS ONLY) Fy = 50 KSI ASTM A325-N (U.N.O.)

© COPYRIGHTED MATERIAL																
	D E	CHITEC	G N CTURE	+EN	GIN	IEEI	U RIN	P IG								
		18 Ho Biloxi, P:	signeo owarc Missis 228.3 npde	d Ave ssipp 888.1	ə Su i 39 950	uite 953())									
AWS.	[Davic Brac Gerroc	I J. Mo d P. P d W. I ord A	acho atar (ilpa	adc 10, I tric	o, Pl PE k, F	E PE	-								
THE COPYRIGHT LAWS		Fernanda A. Silva, AIA														
THE DISCREPANCIES OCCUR, THE ORIGINAL SIGNED STATE DOWNLING THE DRAWINGS, DETAILS, AND NOTES THAT APPEAR ON THIS SHEET ARE COPYRIGHTED BY MACHADO PATANO, PLLC, AND CLAIM ALL RIGHTS OF THE COPYRIGHT LAWS.		A 79 OF P	ENGI ENGI 2-3 #10		Salar W Nos	NOM 100										
TANO, PLLC, AND	ES		*****	11111	· · ·											
BY MACHADO PA	VANCLEAVE SCHOOLS HVAC UPGRADES	DDLE.						39060								
RE COPYRIGHTED	S HVAC I	ARY. MI	HOOLS			WY 57		ושלווטטוט								
ON THIS SHEET A	CHOOLS	LEMENT	HIGH SC	1 E7 170	01, 41 C	8 12424 HWY 57		VE, MISS								
THAT APPEAR	EAVE S	OWER E	<u>8</u>			 ഷ		VAINULEAVE, MISSISSIPPI 39565								
DETAILS, AND NOT	VANCI							>								
THE DRAWINGS,	SCAL PROJI DRAW CHEC	E: AS ECT NO /N BY: KED BY	: 0155 ADC ': GWI	.22.0 <	, 08											
Y OTHER PLANS.	OOL	PAD	പ്													
ALL OVERRIDE AN	RAY SCH	IPMENT	& Detail													
RED PLAN SET SH.	LOWER ELEMENTRAY SCHOOL	MECHANICAL EQUIPMENT PAD	PLAN, SECTIONS, & DETAILS													
) SEALED ENGINEE	LOWER E	MECHAN	PLAN, SE													
DISCREPANCIES OCCUR, THE ORIGINAL SIGNED, DATED AND SEALED ENGINEERED PLAN SET SHALL OVERIDE ANY OTHER PLANS. THE DRAWNGS, DETAILS, AND NOTES THAT APPEAR ON THIS SHEET ARE COPYRIGHTED BY MACHADO PATANO, PLLC, AND NOTES THAT APPEAR ON THIS SHEET ARE COPYRIGHTED BY MACHADO PATANO, PLLC, AND NOTES THAT APPEAR ON THIS SHEET ARE COPYRIGHTED BY MACHADO PATANO, PLLC, AND NOTES THAT APPEAR ON THIS SHEET ARE COPYRIGHTED BY MACHADO PATANO, PLLC, AND NOTES THAT APPEAR ON THIS SHEET ARE COPYRIGHTED BY MACHADO PATANO, PLLC, AND NOTES THAT APPEAR ON THIS SHEET ARE COPYRIGHTED BY MACHADO PATANO, PLLC, AND NOTES THAT APPEAR ON THIS SHEET ARE COPYRIGHTED BY MACHADO PATANO, PLLC, AND NOTES THAT APPEAR ON THIS SHEET ARE COPYRIGHTED BY MACHADO PATANO, PLLC, AND NOTES THAT APPEAR ON THIS SHEET ARE COPYRIGHTED BY MACHADO PATANO, PLLC, AND NOTES THAT APPEAR ON THIS SHEET ARE COPYRIGHTED BY MACHADO PATANO, PLLC, AND NOTES THAT APPEAR ON THIS SHEET ARE COPYRIGHTED BY MACHADO PATANO, PLLC, AND NOTES THAT APPEAR	TTAL	RUCTION														
THE ORIGINAL S	REVISION / SUBMITTAL	02.03.2023 ISSUED FOR CONSTRUCTION														
REPANCIES OCCUR	DATE REV	72.03.2023 ISSI														
	NO.	REV 0 0														
EGISTERED ENGINEER OF RECORD. IF		S	51	0	C											
EGISTERED E	BAR		RIFY		INAL	DRA 1"	w	NG								

F NOT ONE INCH ON THIS SHEET, ADJUST

SCALES ACCORDINGLY




IAL															
© COPYRIGHTED MATERIAL		S I	-	N		-		0	-	<u> </u>					
	9	"De: 18 Ho Biloxi, P:	sigr owc Mis 228	ard ssis 3.3	d to A sip 88	o B ve pi .19	uil Su 39 50	d" iite 53(F D						
HT LAWS.	C	vww.r Davic Brad Gerrod Bradfo Ferno	d J. d P. d W ord	Мс Рс /. К А.	iloc atc atc Jc	na anc ati	do o, F ricl es,	, P PE k, F Al/	E PE	-					
LC, AND CLAIM ALL RIGHTS OF THE COPYRIGHT LAWS.	POD W. KILA R. OD PROFEST W. KILA R. OPROFEST W. KILA M. K														
DETAILS, AND NOTES THAT APPEAR ON THIS SHEET ARE COPYRIGHTED BY MACHADO PATANO, PL	VANCLEAVE SCHOOLS HVAC UPGRADES	LOWER ELEMENTARY. MIDDLE.					VANUCLEAVE, MISSISSIPPI 39365								
HE DRAWINGS, I	SCAL PROJ DRAW CHEC	E: AS ECT NC /N BY: KED BY	IND): 01 AD((; G	1CA 55. C WK	22.	.00	8								
L OVERRIDE ANY OTHER PLANS. T															
AND SEALED ENGINEERED PLAN SET SHAL	HIGH SCHOOL - COOLING TOWER	PLANS, SECTIONS, & DETAILS													
DCUR, THE ORIGINAL SIGNED, DATED AND SEALED ENGINEERED PLAN SET SHALL	BEVISION / SUBMITTAL HIGH SCHOOL - CO	ISSUED FOR CONSTRUCTION PLANS, SECTIONS,													
F DISCREPANCIES OCCUR, THE ORIGINAL SIGNED, DATED AND SEALED ENGINEERED PLAN SET SHAL		02.03.2023 ISSUED FOR CONSTRUCTION													
OF RECORD. IF DISCREPANCIES OCCUR, THE ORIGINAL SIGNED, DATED AND SEALED ENGINEERED PLAN SET SHALL OVERRIDE ANY OTHER PLANS. THE DRAWINGS, DETAILS, AND NOTES THAT APPEAR ON THIS SHEET ARE COPYRIGHTED BY MACHADO PATANO, PLLC,	REVISION / SUBMITTAL	ISSUED FOR CONSTRUCTION													
THE REGISTERED ENGINEE OF RECORD. IF DISCREPANCIES OCCUR, THE ORIGINAL SIGNED, DATED AND SEALED ENGINEERED PLANS. THE DRAWINGS, DETAILS, AND NOTES THAT APPEAR ON THIS SHEET ARE COPYRIGHTED BY MACHADO PATANO, PLLC,	REVISION / SUBMITTAL	REV 0 02.03.2023 ISSUED FOR CONSTRUCTION		1											

	HVAC SYMBOLS
	SQUARE/RECTANGULAR SUPPLY DOWN
	SQUARE/RECTANGULAR SUPPLY UP
	ROUND SUPPLY DOWN
	ROUND SUPPLY UP
	SQUARE/RECTANGULAR RETURN DOWN
	SQUARE/RECTANGULAR RETURN UP
	ROUND RETURN DOWN
	ROUND RETURN UP
	SQUARE/RECTANGULAR EXHAUST DOWN
	SQUARE/RECTANGULAR EXHAUST UP
	ROUND EXHAUST DOWN
	ROUND EXHAUST UP
	SQUARE/RECTANGULAR ELBOW
	SQUARE/RECTANGULAR ELBOW WITH TURNING VANES
	ROUND MAIN WITH CONICAL TAKEOFF
	ROUND MAIN WITH CONICAL TEE
	SQUARE/RECTANGULAR MAIN WITH CONICAL TEE
	ROUND MAIN WITH 45° LATERAL WYE
	SQUARE/RECTANGULAR MAIN WITH 45° LEAD IN TAKEOFF
	ROUND ELBOW
	EXISTING DUCT TO BE REMOVED
	EXISTING DUCT TO REMAIN
	NEW DUCT
	FLEXIBLE DUCT
	MANUAL VOLUME DAMPER
	INTERNALLY INSULATED DUCT
	SQUARE/RECTANGULAR TO ROUND TRANSITION
	CONCENTRIC TRANSITION
	ECCENTRIC TRANSITION
	ROUND NECK CEILING AIR TERMINAL
	SQUARE/RECTANGULAR NECK CEILING AIR TERMINAL
- ~~	TRANSFER AIR PATH
Ģ	TIMECLOCK
Φ	THERMOSTAT
Ş	TEMPERATURE SENSOR
Ĥ	HUMIDITY SENSOR
SD	DUCT SMOKE DETECTOR
•	CONNECT TO EXISTING
\$	SWITCH
MD	MOTORIZED DAMPER
FD	FIRE DAMPER
FSD	COMBINATION FIRE/SMOKE DAMPER
SD	SMOKE DAMPER
BDD	BACKDRAFT DAMPER
	CAP AND SEAL
20000	FLEXIBLE CONNECTION

	HVAC	; A
	A	
А	AMPS	
AC	AIR CONDITIONING	
AFF	ABOVE FINISHED FLOOR	
AHU	AIR HANDLING UNIT	
AL	ALUMINUM	
	В	
BDD	BACKDRAFT DAMPER	
BOD	BOTTOM OF DUCT	
	С	
CEF	CEILING EXHAUST FAN	
CFH	CUBIC FEET PER HOUR	
CFM	CUBIC FEET PER MINUTE	
CHW	CHILLED WATER	
CHWR	CHILLED WATER RETURN	
CHWS	CHILLED WATER SUPPLY	
CU	CONDENSING UNIT	
CW	CONDENSER WATER	
CWS	CONDENSER WATER SUPPLY	
CWR	CONDENSER WATER RETURN	
	D	
DC	DIRECT CURRENT	
	E	
Ε	EXISTING	
EA	EXHAUST AIR	
EC	ELECTRICAL CONTRACTOR	
EC	EXHAUST FAN	
ESP	EXTERNAL STATIC PRESSURE	
	F	
FC	FAN COIL	
FD	FIRE DAMPER	
FSD	COMBINATION FIRE/SMOKE DAMPER	
FT	FOOT/FEET	
	G	
GA	GAUGE	
GC	GENERAL CONTRACTOR	
GFM	GLASS FABRIC AND MASTIC	
	Н	
HP	HORSEPOWER OR HEAT PUMP	
HW	HOT WATER	
HWR	HOT WATER RETURN	
HWS	HOT WATER SUPPLY	
	K	
KW	KILOWATT	
	Ĺ	
LBS	POUNDS	

	M						
MAX	MAXIMUM						
MBH	ONE THOUSAND BRITISH THERMAL UNITS PER HOUR						
МС	MECHANICAL CONTRACTOR						
MCA	MINIMUM CIRCUIT AMPACITY						
MD	MOTORIZED DAMPER						
MIN	MINIMUM						
MOCP MAXIMUM OVERCURRENT PROTECTION							
Ν							
NC/P0	NORMALLY CLOSED/POWERED OPEN						
NIC	NOT IN CONTRACT						
NIS	NEOPRENE IN SHEAR						
N0/PC	NORMALLY OPEN/POWERED CLOSED						
NTS	NOT TO SCALE						
	0						
OA	OUTDOOR AIR						
OC	ON CENTER						
	P						
PC PLUMBING CONTRACTOR							
PH	PHASE						
R							
RA	RETURN AIR						
RFD	ROUND FIRE DAMPER						
RGS	RIGID SEALED						
RIS	RUBBER IN SHEAR REVOLUTIONS PER MINUTE						
RPM							
	S						
SA	SUPPLY AIR						
SFD	SQUARE FIRE DAMPER						
SQFT	SQUARE FEET						
	Т						
TSP	TOTAL STATIC PRESSURE						
TYP	TYPICAL						
	U						
UC	UNDERCUT DOOR						
UL	UNDERWRITERS LABORATORIES						
	V						
V	VOLTAGE						
VD	VOLUME DAMPER						
VIF	VERIFY IN FIELD						
	W						
W	WATT						
**	WATER COLUMN						

HVAC ABBREVIATIONS



A.		ALL WORK SHALL CONFORM TO THE LATEST EDITIONS OF THE INTERNATIONAL CODE AND ALL LOCAL		c. Al M J(
	2.	ORDINANCES AS ADOPTED BY THE LOCAL JURISDICTION. CONTRACTOR SHALL PROVIDE ALL MATERIALS AND LABOR NECESSARY FOR THE COMPLETE INSTALLATION AND OPERATION OF THE SYSTEMS INDICATED ON THE CONTRACT DOCUMENTS AND		d. Al
	3.	DRAWINGS EVEN IF NOT SPECIFICALLY SHOWN. THE DRAWINGS ARE, IN PART, DIAGRAMMATIC AND DO NOT ALWAYS SHOW ALL NECESSARY MATERIALS	C.	INSULATIO
		AND EQUIPMENT TO SCALE OR IN EXACT LOCATIONS. IT IS THE CONTRACTORS RESPONSIBILITY TO CHECK ALL MEASUREMENTS, COORDINATE ALL WORK WITH OTHER TRADES, REVIEW ALL ARCHITECTURAL AND STRUCTURAL DRAWINGS, AND VISIT THE JOBSITE TO MAKE APPROPRIATE MEASUREMENTS.		1. ALL S 2. ALL E CONS
	4.	CONTRACTOR SHALL OBTAIN ALL NECESSARY PERMITS AND INSPECTIONS AND SHALL PAY ALL ASSOCIATED FEES FOR SCOPE OF WORK.		3. ALL C SHALL
	5.	WHEN THE SPECIFICATIONS OR DRAWINGS ARE UNCLEAR OR IN CONFLICT WITH CODES OR OTHER TRADES, THE CONTRACTOR SHALL BRING THIS TO THE ATTENTION OF THE ENGINEER FOR CLARIFICATION BEFORE SUBMITTING A BID.		4. INTER a. W
	6.	SUBMITTALS AND SHOP DRAWINGS FOR ALL EQUIPMENT, MATERIALS, AND ACCESSORIES SHALL BE PROVIDED TO THE OWNER AND ENGINEER FOR REVIEW AND COMMENT PRIOR TO ORDER, MANUFACTURE, FABRICATION, AND INSTALLATION. FAILURE TO DO SO SHALL NOT RELIEVE THIS CONTRACTOR OF THE RESPONSIBILITY, CONSEQUENCES, AND POSSIBLE COSTS OF SUCH ACTION OR LACK OF ACTION REGARDLESS OF ANY AND ALL ERRORS OR OMISSIONS ON THESE DOCUMENTS. THIS ENGINEER SHALL NOT BE HELD LIABLE FOR ANY COSTS ASSOCIATED WITH THIS CONTRACTOR'S FAILURE TO COMPLY WITH THIS ITEM. IF SUBSTITUTIONS FOR SPECIFIED ITEMS ARE MADE, IT IS THIS CONTRACTOR'S RESPONSIBILITY TO PROVE PERFORMANCE, COMPATIBILITY, AND CONFORMANCE WITH THE ORIGINAL DESIGN AND SPECIFICATIONS. RE-DESIGN BY THIS ENGINEER TO ACCOMMODATE SUBSTITUTIONS SHALL NOT BE PERFORMED. OTHERWISE, IT WILL BE CONSIDERED ADDITIONAL WORK FOR WHICH COMPENSATION WILL BE REQUIRED.		IN b. W IN O c. TI O 5. ALL S THICK
	7.	ALL ACTUAL EQUIPMENT, MATERIALS, AND ACCESSORIES TO BE INSTALLED SHALL BE FULLY COORDINATED WITH THE ELECTRICAL, PLUMBING, CIVIL, STRUCTURAL, AND ARCHITECTURAL CONTRACTORS PRIOR TO ORDER, MANUFACTURE, FABRICATION, AND INSTALLATION. THIS INCLUDES BUT IS NOT LIMITED TO ELECTRICAL DATA, WEIGHTS, PLUMBING REQUIREMENTS, DIMENSIONS, PENETRATIONS, ETC. FAILURE TO DO SO SHALL NOT RELIEVE THIS CONTRACTOR OF THE RESPONSIBILITY, CONSEQUENCES, AND POSSIBLE COSTS OF SUCH ACTION OR LACK OF ACTION REGARDLESS OF ANY AND ALL ERRORS OR OMISSIONS ON THESE DOCUMENTS. THIS ENGINEER SHALL NOT BE HELD LIABLE FOR ANY COSTS ASSOCIATED WITH THIS CONTRACTORS FAILURE TO COMPLY WITH THIS ITEM.		 ALL C LINES REFRI CELLL ALL J BUILD EXPOS TIGHT
	8.	ANY AND ALL DEVIATIONS FROM THE DESIGN DOCUMENTS WITHOUT THIS ENGINEER'S APPROVAL INDICATES ACCEPTANCE BY THIS CONTRACTOR AND/OR OWNER FOR THE RESPONSIBILITY OF THE PERFORMANCE OF THE SYSTEM AFFECTED. THIS ENGINEER SHALL NOT BE HELD LIABLE FOR ANY COSTS ASSOCIATED WITH THIS CONTRACTOR'S FAILURE TO FOLLOW THE DESIGN DOCUMENTS. IF MODIFICATIONS TO THE SPECIFIED DESIGN ARE MADE, IT IS THIS CONTRACTOR'S RESPONSIBILITY TO PROVE PERFORMANCE, COMPATIBILITY, AND CONFORMANCE WITH THE ORIGINAL DESIGN AND SPECIFICATIONS. RE-DESIGN BY THIS ENGINEER TO ACCOMMODATE MODIFICATIONS SHALL NOT BE PERFORMED. OTHERWISE, IT WILL BE CONSIDERED ADDITIONAL WORK FOR WHICH COMPENSATION WILL BE REQUIRED. SITE VISITS, INSPECTIONS, CALCULATIONS, COORDINATION, ETC. PERFORMED BY THIS ENGINEER TO INVESTIGATE PROBLEMS ASSOCIATED WITH DESIGN DEVIATIONS WILL ALSO BE CONSIDERED ADDITIONAL WORK FOR WHICH COMPENSATION WILL BE REQUIRED.	D.	REFRIGER 1. ALL F DRAWI ASTM 2. ALL F HARD TO AS 3. ALL F
	9.	ANY ERRORS OR OMISSIONS ON THESE DOCUMENTS SHALL BE IMMEDIATELY BROUGHT TO THE ATTENTION OF THE ENGINEER FOR REVIEW AND CORRECTION.		4. ALL S
	10.	THE CONSTRUCTION DOCUMENTS ARE COMPRISED OF BOTH DRAWINGS AND SPECIFICATIONS (PROJECT MANUAL). ALL TRADES ARE INTERDEPENDENT AND MUST BE FULLY COORDINATED TO PROVIDE A COMPLETE PROJECT. THE GENERAL CONTRACTOR SHALL NOT BREAK OUT INDIVIDUAL SECTIONS TO SUB–CONTRACTORS OR VENDORS.		DIREC 5. IF SO
	11.	THE CONTRACTOR IS RESPONSIBLE FOR COORDINATING WORK OF ALL TRADES TO INSURE A USABLE & FUNCTIONAL END PRODUCT. ANY CONFLICTS BETWEEN THE DRAWINGS AND SPECIFICATIONS SHALL BE CLARIFIED BY THE ARCHITECT/ENGINEER. IF NO CLARIFICATION IS ISSUED THE BIDDER SHALL BID THE MOST STRINGENT PRODUCT OR APPLICATION.	E. F.	EXCES THERMOS [®] A CERTIFI
	12.	IF DISCREPANCIES ARE ENCOUNTERED BETWEEN THE DRAWINGS AND SPECIFICATIONS, THE MOST STRINGENT PRODUCT OR APPLICATION OVERRIDES IN ALL CASES.		COMPANY UNITS SH WITHIN 59
	13.	THIS ENGINEER SHALL NOT BE HELD LIABLE FOR COSTS ASSOCIATED WITH ERRORS AND/OR OMISSIONS ON THESE DOCUMENTS IN EXCESS OF THE COST AND/OR TIME FOR THIS ENGINEER TO CORRECT THE DOCUMENTS. IN ANY CASE, THE LIMIT OF LIABILITY FOR THIS ENGINEER SHALL BE NO MORE THAN THE COST OF THIS ENGINEER'S INDIVIDUAL FEE, REGARDLESS OF THE TOTAL DESIGN FEE CHARGED FOR THE SET OF CONSTRUCTION DOCUMENTS.	G.	AND THIS ALL LINE AND INTE EXCEPT T CONTRACT INTERCON
	14.	TO THE FULLEST EXTENT PERMITTED BY LAW, THE TOTAL LIABILITY IN THE AGGREGATE, OF THIS ENGINEER AND THIS ENGINEER'S OFFICERS, DIRECTORS, EMPLOYEES, AGENTS, AND INDEPENDENT PROFESSIONAL ASSOCIATES, AND ANY OF THEM, TO OWNER AND ANY ONE CLAIMING BY, THROUGH OR UNDER OWNER, FOR ANY AND ALL INJURIES, CLAIMS, LOSSES, EXPENSES, OR DAMAGES WHATSOEVER ARISING OUT OF OR IN ANY WAY RELATED TO THIS ENGINEER'S SERVICES, THE PROJECT OR THESE DOCUMENTS, FROM ANY CAUSE OR CAUSES WHATSOEVER, INCLUDING BUT NOT LIMITED TO, THE NEGLIGENCE, ERRORS, OMISSIONS, STRICT LIABILITY, BREACH OF CONTRACT, MISREPRESENTATION, OR BREACH OF WARRANTY OF THIS ENGINEER; OR THIS ENGINEER'S OFFICERS, DIRECTORS, EMPLOYEES, AGENTS OR INDEPENDENT PROFESSIONAL ASSOCIATES, OR ANY OF THEM, SHALL NOT EXCEED THE TOTAL COMPENSATION RECEIVED BY THIS ENGINEER FOR SERVICES PROVIDED.	н.	EXCEPT T THE FIRE PROVIDED COORDINA REFRIGER 1. PRESS a. IN
	15.	THE USE OF THESE DOCUMENTS FOR CONSTRUCTION SIGNIFIES THIS OWNER, TENANT, AND CONTRACTORS AGREEMENT WITH THE ABOVE REQUIREMENTS REGARDLESS OF ANY OTHER PRIOR, CURRENT, OR FUTURE AGREEMENT AND/OR CONTRACT.		a.
	16.	ALL EQUIPMENT, PRODUCTS, MATERIALS, COMPONENTS, ACCESSORIES, ETC. SHALL BE MANUFACTURED IN THE USA.		b. El
В.		CTWORK		b. b.
	1.	TURNING VANES SHALL BE INSTALLED IN ALL RECTANGULAR/SQUARE ELBOWS AND TEES 45" OR LARGER.		D.
		ALL DUCTWORK SHALL BE SHEET METAL CONSTRUCTION. ALL SHEET METAL DUCT CONNECTIONS TO ANY FAN POWERED EQUIPMENT SHALL BE MADE WITH		2. VACUI a. F(
		FLEXIBLE DUCT CONNECTORS 3" MIN IN LENGTH.		TI
	4.	LOW PRESSURE DUCTWORK a. ALL SUPPLY DUCTWORK AND RETURN DUCTWORK SHALL BE CONSTRUCTED TO 2" WG PRESSURE CLASS STANDARDS AND SHALL CONFORM TO THE LATEST EDITIONS OF THE SMACNA DUCT CONSTRUCTION STANDARDS.		b. C M E c. M
		 b. ALL SUPPLY, RETURN, AND EXHAUST DUCTWORK SHALL BE GALVANIZED SHEET METAL CONSTRUCTION UNLESS OTHERWISE NOTED IN THIS SECTION. SHEET METAL GAUGE SHALL BE AS PER SMACNA DUCT CONSTRUCTION STANDARDS (28 GAUGE OR LESS DEPENDING ON SIZE AND SHAPE). 30 GAUGE OR HIGHER SHEET METAL DUCT IS NOT ACCEPTABLE 		3. FOLLC RECO ACID,

HVAC NOTES

- ALL EXTERNALLY INSULATED SHEET METAL DUCTWORK JOINTS SHALL BE SEALED AIRTIGHT WITH MASTIC AND TAPED OVER WITH DUCT TAPE. ALL INTERNALLY INSULATED SHEET METAL DUCTWORK JOINTS SHALL BE SEALED AIRTIGHT WITH MASTIC AND THE EXTERIOR SURFACE WIPED CLEAN TO PROVIDE A FINISHED APPEARANCE.
- ALL SQUARE AND RECTANGULAR VOLUME DAMPERS SHALL BE OPPOSED BLADE TYPE.
- SUPPLY, RETURN, AND OUTDOOR AIR DUCTWORK SHALL BE INSULATED.
- EXPOSED SUPPLY, RETURN, AND OUTDOOR AIR DUCTWORK SHALL BE SHEET METAL NSTRUCTION AND SHALL BE INTERNALLY INSULATED.
- L CONCEALED SHEET METAL AND FLEXIBLE SUPPLY, RETURN, AND OUTDOOR AIR DUCTWORK ALL BE EXTERNALLY INSULATED, UNLESS INTERNALLY LINED.
- ERNAL DUCT INSULATION
- WHERE INDICATED ON THE PLANS, SHEET METAL DUCTWORK SHALL BE INTERNALLY LINED WITH INSULATION.
- WHEN INSTALLED IN FULLY CONDITIONED SPACES AND RETURN AIR PLENUMS WITHIN THE INSULATED AND/OR CONDITIONED ENVELOPE, INTERNAL INSULATION SHALL BE 1" THICK UNLESS OTHERWISE SPECIFIED.
- THE FIRST 10'-0" OF RECTANGULAR/SQUARE SHEET METAL DUCT UPSTREAM OR DOWNSTREAM OF ANY FAN SHALL BE INTERNALLY INSULATED WHETHER OR NOT INDICATED IN PLAN.
- L SUPPLY, RETURN, AND OUTDOOR AIR DUCTWORK SHALL BE EXTERNALLY INSULATED WITH 2" ICK INSULATION (R-6.0), UNLESS INTERNALLY LINED. ALL JOINTS SHALL BE SEALED.
- CONDENSATE PIPING WITHIN THE BUILDING ENVELOPE, INCLUDING PRIMARY AND SECONDARY ES, SHALL BE INSULATED WITH 1/2" THICK PIPE INSULATION. ALL JOINTS SHALL BE SEALED.
- FRIGERANT SUCTION PIPING LESS THAN 1-1/2" SHALL BE INSULATED WITH 1/2" THICK FLEXIBLE LLULAR INSULATION. PIPING 1-1/2" OR LARGER SHALL BE INSULATED WITH 1" THICK INSULATION. _ JOINTS SHALL BE SEALED. LIQUID LINES SHALL BE INSULATED WHEN INSTALLED WITHIN THE ILDING IN UNCONDITIONED SPACES OUTSIDE OF THE INSULATED AND/OR CONDITIONED ENVELOPE.
- POSED EXTERIOR PIPE INSULATION SHALL BE JACKETED WITH ALUMINUM AND SEALED WEATHER

ERANT PIPING


- _ REFRIGERANT PIPING 1–3/8" AND SMALLER SHALL BE TYPE L–ACR OR TYPE K–ACR HARD AWN OR SOFT (AS INDICATED) COPPER UL RATED FOR 700 PSI AT 250°F AND CONFORMING TO TM STANDARD B280.
- L REFRIGERANT PIPING LARGER THAN 1-3/8" AND 2-5/8" OR LESS SHALL BE TYPE K-ACR RD DRAWN OR SOFT (AS INDICATED) COPPER UL RATED TO 700 PSI AT 250°F AND CONFORMING ASTM STANDARD B280.
- REFRIGERANT PIPE FITTINGS SHALL BE WROT COPPER UL RATED TO 700 PSI AT 250°F AND ALL MEET ANSI/ASME STANDARD B16.22 AND NSF 61G.
- STRAIGHT RUNS OF REFRIGERANT PIPING SHALL BE SLOPED 1/8" PER FOOT MIN IN THE RECTION OF FLOW.
- SOFT COPPER TUBING IS USED, IT SHALL BE INSTALLED AS STRAIGHT AS POSSIBLE WITHOUT CESSIVE BENDS, KINKS, OR OTHER OBSTRUCTIONS.
- OSTATS SHALL BE COMPATIBLE WITH SCHOOL CONTROL SYSTEM.
- TIFIED TEST AND BALANCE SHALL BE PERFORMED BY A CERTIFIED, 3RD PARTY TEST AND BALANCE NY. INDIVIDUAL GRILLES SHALL BE BALANCED TO WITHIN 10% OF THE DESIGN AIR FLOWS AND SHALL BE BALANCED TO WITHIN 5% OF THE DESIGN AIR FLOWS. PUMPS SHALL BE BALANCED TO 5% OF THE DESIGN FLOW. THE TEST AND BALANCE REPORT SHALL BE PROVIDED TO THE OWNER HIS ENGINEER FOR REVIEW AND COMMENT.
- NE VOLTAGE (120V, 240V, 460V, ETC.) CONTROLS (SWITCHES, TIME CLOCKS, ETC.), ACCESSORIES, ITERCONNECTING WIRING SHALL BE PROVIDED AND INSTALLED BY THE ELECTRICAL CONTRACTOR I THAT ALL DAMPER ACTUATORS SHALL BE PROVIDED AND INSTALLED BY THE MECHANICAL ACTOR. ALL LOW VOLTAGE (24V, ETC.) CONTROLS (THERMOSTATS, ETC.), ACCESSORIES, AND ONNECTING WIRING SHALL BE PROVIDED AND INSTALLED BY THE MECHANICAL CONTRACTOR I THAT ALL ASSOCIATED SMOKE AND FIRE ALARM WIRING SHALL BE PROVIDED AND INSTALLED BY RE ALARM CONTRACTOR. ALL NECESSARY TRANSFORMERS (120V TO 24V, ETC.) SHALL BE VED AND INSTALLED BY THE MECHANICAL CONTRACTOR OR THEIR CONTROLS SUBCONTRACTOR. INATE ALL WORK WITH THE ELECTRICAL AND FIRE ALARM CONTRACTORS.
- ERANT SYSTEM TESTS


ESSURE TEST

- INTERCONNECTING PIPING
- a.1. EVACUATE ALL REFRIGERANT FROM THE SYSTEM.
- a.2. ISOLATE THE COMPONENT INTERCONNECTING PIPING AND CHARGE WITH DRY, OXYGEN FREE NITROGEN (OFN) TO 1.3 TIMES THE MAXIMUM ALLOWABLE PRESSURE OF THE SYSTEM COMPONENTS. MAINTAIN PRESSURE FOR 12 HOURS. IF LOSS OF PRESSURE OCCURS, LOCATE AND REPAIR LEAKS AND REPEAT TEST PROCEDURE.
- ENTIRE SYSTEM
- b.1. EVACUATE ALL REFRIGERANT FROM THE SYSTEM.
- b.2. CHARGE SYSTEM WITH DRY OFN TO THE MAXIMUM ALLOWABLE PRESSURE OF THE SYSTEM COMPONENTS. MAINTAIN PRESSURE FOR 12 HOURS. IF LOSS OF PRESSURE OCCURS, LOCATE AND REPAIR LEAKS AND REPEAT TEST PROCEDURE.
- UUM TEST
- FOLLOWING SUCCESSFUL PRESSURE TESTING, EVACUATE THE SYSTEM TO 1500 MICRON. BREAK THE VACUUM WITH DRY OFN TO 1 BAR. REPEAT ONCE.
- CONTINUOUSLY EVACUATE THE SYSTEM TO BETWEEN 300 MICRON AND 500 MICRON FOR A MINIMUM OF 1 HOUR. INSPECT VACUUM PUMP FOR SIGNS OF MOISTURE DISCHARGE. CONTINUE EVACUATION AND INSPECT AT 1 HOUR INTERVALS UNTIL MOISTURE IS NOT PRESENT.
- MAINTAIN VACUUM FOR FOR 12 HOURS. IF LOSS OF VACUUM OCCURS, REPEAT TEST PROCEDURE.

LOWING SUCCESSFUL PRESSURE AND VACUUM TESTING, CHARGE SYSTEM WITH NEW REFRIGERANT. COVERED, RECYCLED, OR RECLAIMED REFRIGERANT SHALL BE TREATED TO REMOVE MOISTURE, OIL, D, AND PARTICULATE MATTER PRIOR TO USE. 4. DOCUMENT TESTING AND PROVIDE TO OWNER. INSPECTION BY LOCAL AUTHORITY MAY BE REQUIRED.I. CONDENSATE PIPING


- 1. ALL CONDENSATE PIPING SHALL BE PROVIDED AND INSTALLED BY THE MECHANICAL CONTRACTOR.
- 2. MATERIAL
- a. INTERIOR CONDENSATE PIPING SHALL BE APPROVED, SCHEDULE 40 PVC WITH PVC FITTINGS AND SOLVENT CEMENT JOINTS UNLESS OTHERWISE NOTED.
- b. EXTERIOR CONDENSATE PIPING SHALL BE APPROVED, SCHEDULE 80 PVC WITH PVC FITTINGS AND SOLVENT CEMENT JOINTS UNLESS OTHERWISE NOTED.
- c. WHEN NOTED AND/OR WHEN INSTALLED IN A RETURN AIR PLENUM CONDENSATE PIPING SHALL BE TYPE M COPPER WITH WROT COPPER FITTINGS AND SOLDERED JOINTS.
- 3. SIZING-CONNECTED LOAD
- a. 2 TONS OR LESS=3/4"
- b. MORE THAN 2 TONS TO 5 TONS=1"
- c. MORE THAN 5 TONS TO 30 TONS=1-1/4"
- 4. MINIMUM SLOPE
- a. 2–1/2" OR LESS=1/4" PER FOOT
- J. ALL PIPING SHALL BE LABELED IN ACCORDANCE WITH ASTM STANDARD A13.1. LABELS SHALL INCLUDE PIPING SERVICE (REFRIGERANT SUCTION, REFRIGERANT LIQUID, CONDENSATE, ETC.), SIZE, AND DIRECTION OF FLOW.
- K. COORDINATE ALL REQUIRED WALL, FLOOR, CEILING, AND ROOF PENETRATION LOCATIONS AND SIZES WITH THE GC PRIOR TO CONSTRUCTION. GC SHALL PROVIDE ALL REQUIRED FRAMED OPENINGS, HEADERS, MASONRY OPENINGS, LINTELS, ETC. AS NECESSARY.
- L. COORDINATE ALL DUCT LOCATIONS, SIZES, AND ROUTING WITH GC PRIOR TO CONSTRUCTION. GC SHALL PROVIDE A CLEAR PATH THROUGH FRAMING AND MASONRY COMPONENTS TO ACCOMMODATE DUCT ROUTING.
- M. COORDINATE ALL DUCT AND PIPE LOCATIONS, SIZES, AND ROUTING PRIOR TO CONSTRUCTION.
- N. WATER SYSTEMS SHALL BE FLUSHED WITH CLEAN POTABLE WATER PRIOR TO SYSTEM START UP. FOLLOWING SYSTEM START UP BUT PRIOR TO TESTING AND BALANCING, ALL STRAINERS AND FILTERS SHALL BE FLUSHED AND CLEANED SO THEY ARE FREE OF DEBRIS. ENSURE THAT ALL COILS, PUMPS, EQUIPMENT, ETC. HAVE HAD FULL WATER FLOW PRIOR TO STRAINER/FILTER BLOW DOWN.
- O. A QUALIFIED WATER TREATMENT SPECIALIST SHALL TEST AND TREAT ALL CONDENSER WATER SYSTEMS PRIOR TO SYSTEM TURN OVER TO OWNER TO PREVENT CORROSION, SCALE, BIOLOGICAL CONTAMINANTS, ETC.. CHEMICALS AND CONCENTRATIONS USED SHALL BE COMPATIBLE WITH PIPING AND EQUIPMENT MATERIALS.
- P. LARGE EQUIPMENT SHALL BE SHIPPED FROM THE FACTORY IN SECTIONS SMALL ENOUGH TO FIT THROUGH ALL OPENINGS REQUIRED FOR INSTALLATION. BREAKDOWN OF EQUIPMENT ON SITE SHALL NOT BE PERMITTED. EQUIPMENT SHALL BE PROVIDED WITH DETAILED FACTORY PROVIDED INSTRUCTIONS FOR REASSEMBLY AND CONTRACTOR SHALL COMPLY WITH ALL REQUIREMENTS, MATERIALS, WORKMANSHIP, ETC. COORDINATE WITH EQUIPMENT MANUFACTURERS, ARCHITECTURAL PLANS, AND WITH GC. REASSEMBLY OF EQUIPMENT SHALL BE PART OF THIS CONTRACT AND NO CHANGE ORDERS SHALL BE ALLOWED FOR FAILURE TO COMPLY WITH THIS SECTION.
- Q. ALL PIPING CONNECTIONS AT MOTORIZED EQUIPMENT SHALL HAVE BRAIDED STAINLESS STEEL FLEXIBLE CONNECTIONS. PROVIDE WITH DIELECTRIC UNIONS FOR COPPER PIPE AND CONNECTIONS.
- ALL CONTROL COMPONENTS, ACCESSORIES, AND INTERCONNECTING WIRING SHALL BE PROVIDED AND INSTALLED BY THE MECHANICAL CONTRACTOR OR HIS CONTROLS SUBCONTRACTOR. 120V POWER SHALL BE BROUGHT TO CONTROL COMPONENTS AS NECESSARY BY THE ELECTRICAL CONTRACTOR. COORDINATE ALL WORK WITH THE ELECTRICAL CONTRACTOR.
- S. CONTRACTOR SHALL PROCURE THE SERVICES OF THE SCHOOL'S EXISTING CONTROLS CONTRACTOR (SEIMENS) TO FULLY INTEGRATE THE NEW/REPLACED EQUIPMENT INTO THE EXISTING CONTROL SYSTEM. THIS SHALL INCLUDE ALL PROGRAMMING, CONTROLLERS, CONTROL CABINETS, GRAPHICS, LOW VOLTAGE WIRING, SOFTWARE, HARDWARE, SENSORS, ETC. AS NECESSARY.
- T. THE CONTROLS CONTRACTOR SHALL PROVIDE AND INSTALL ALL LOW VOLTAGE EQUIPMENT, COMPONENTS, AND WIRING.
- U. 120V POWER SHALL BE BROUGHT TO CONTROL COMPONENTS AS NECESSARY BY THE ELECTRICAL CONTRACTOR. COORDINATE ALL WORK WITH THE ELECTRICAL AND FIRE ALARM CONTRACTORS.
- V. VARIABLE FREQUENCY DRIVES (VFDs) SHALL BE PROVIDED BY THE MECHANICAL OR CONTROLS CONTRACTOR AND SHALL BE INSTALLED BY THE ELECTRICAL CONTRACTOR.
- W. LOW VOLTAGE CONTROL WIRING CONDUIT/RACEWAYS SHALL BE PROVIDED AND INSTALLED BY THE CONTROLS CONTRACTOR. ALL LOW VOLTAGE CONTROL WIRING IN EXPOSED AREAS (MECHANICAL ROOMS, ETC.) SHALL BE INSTALLED IN CONDUIT. ALL LOW VOLTAGE CONTROL WIRING IN CONCEALED AREAS (ABOVE CEILINGS, ETC.) SHALL BE PROPERLY SUPPORTED FROM STRUCTURE WITH J-HOOKS.
- X. ALL TEMPERATURE, HUMIDITY, ETC. SENSORS AND PORTS SHALL BE PROVIDED AND INSTALLED BY THE CONTROLS CONTRACTOR.
- Y. ALL NECESSARY 120V TO LOW VOLTAGE TRANSFORMERS SHALL BE PROVIDED AND INSTALLED BY THE CONTROLS CONTRACTOR.
- Z. ION GENERATORS SHALL BE PROVIDED AND INSTALLED BY THE MECHANICAL CONTRACTOR. THEY SHALL BE WIRED BY THE CONTROLS CONTRACTOR.
- AA. CONDENSATE OVERFLOW SWITCHES SHALL BE PROVIDED AND INSTALLED BY THE MECHANICAL CONTRACTOR. THEY SHALL BE WIRED BY THE CONTROLS CONTRACTOR.
- AB. DUCT SMOKE DETECTORS SHALL BE PROVIDED AND INSTALLED BY THE CONTROLS CONTRACTOR. ALL UNITS OVER 2000 CFM SHALL HAVE RETURN DUCT MOUNTED SMOKE DETECTORS. CONTROLS CONTRACTOR SHALL VERIFY ALL RETURN DUCT SMOKE DETECTORS ARE COMPATIBLE WITH THE FIRE ALARM SYSTEM. SMOKE DETECTORS SHALL BE ADDRESSABLE AND ABLE TO BE MONITORED BY THE FIRE ALARM SYSTEM. WIRING FOR SIGNAL TO THE FIRE ALARM PANEL SHALL BE PROVIDED AND INSTALLED BY THE FIRE ALARM CONTRACTOR. COORDINATE WITH FIRE ALARM CONTRACTOR.
- AC. THE ROOFTOP AC UNITS HAVE FACTORY PROVIDED CONTROLLERS. THE CONTROLS CONTRACTOR SHALL PROVIDE AND INSTALL INTEGRATION OF THESE CONTROLLERS INTO THE BAS. COORDINATE WITH THE MANUFACTURER.
- AD. ALL WORK SHALL BE CAREFULLY COORDINATED BETWEEN THE CONTROLS CONTRACTOR, MECHANICAL CONTRACTOR, ELECTRICAL CONTRACTOR, FIRE ALARM CONTRACTOR, TEST AND BALANCE CONTRACTOR, AND ALL WORK DEPICTED ON THE DRAWINGS AND SPECIFICATIONS.
- AE. THE CONTROLS CONTRACTOR SHALL BE COPIED ON ALL EQUIPMENT SUBMITTALS RELATIVE TO THEIR WORK (PUMPS, AC UNITS, COOLING TOWER, ETC.) FOR REVIEW AND COMMENT. COORDINATE WITH MECHANICAL CONTRACTOR.





1-

LOWER ELEMENTARY SCHOOL MECHANICAL SITE PLAN






MIDDEL SCHOOL MECHANICAL SITE PLAN SCALE: 1/32"=1'-0"


1



































										PACK	AGE ROOF		CHEDULE									
							(COOLING CAPAC	XITY		HEAT											1
TAG	MAKE	MODEL	CFM	ОА	ESP	RPM N	NET TOTAL NE (MBH)	ET SENSIBLE (MBH)	EDB EWB (°F) (°F)		PUT V/ BH)	PH INDOOR FAN HF	P FAN FLA		R COMPRE A AMF		FLA	MCA	МОСР	LBS	NOTES	
HS-RTU-1	DAIKIN	MPS026G	8000	1200	0.60	1162	273.280	197.034	80.0 67.0	95.0	600 460	/3 5	6.6	(3) 2.0	(3) 1	12.2	50.1	53.2	60	4010	2,4,5,6,7,8,9,10,11,12,13,14,15,16,17,18,19,20,21	
HS-RTU-2	DAIKIN	MPS026G	8000	1200	0.60	1162	273.280	197.034	80.0 67.0	95.0	500 460	/3 5	6.6	(3) 2.0	(3) 1	12.2	50.1	53.2	60	4010	2,4,5,6,7,8,9,10,11,12,13,14,15,16,17,18,19,20,21	
HS-RTU-3	DAIKIN	MPS026G	8000	1200	0.60	1162	273.280	197.034	80.0 67.0	95.0	500 460	/3 5	6.6	(3) 2.0	(3) 1	12.2	50.1	53.2	60	4010	2,4,5,6,7,8,9,10,11,12,13,14,15,16,17,18,19,20,21	
HS-RTU-4	DAIKIN	MPS026G	8000	1200	0.60	1162	273.280	197.034	80.0 67.0	95.0	500 460	/3 5	6.6	(3) 2.0	(3) 1	12.2	50.1	53.2	60	4010	1,4,5,6,7,8,9,10,11,12,13,14,15,16,17,18,19,20,21	
HS-RTU-5	DAIKIN	DSP010A	4000	600	0.60	1504	128.365	98.082	80.0 67.0	95.0	I/A 460	/3 8	6.8	(2) 1.8	4.5 &	: 7.9	21.0	23.0	30	2171	3,4,5,6,7,8,9,10,11,12,13,14,15,16,17,18,19,20,21	
1	WITH TRAN	SITION CURB FO	OR COLEMAN	MODEL ZS-2	20N30B4H2AA	B1B1							2 WITH TRANSITION	N CURB FOR Y	ORK MODEL DM24	40N24D4BUA1C						
3	WITH TRAN	SITION CURB FO	OR TRANE MO	DDEL TSC1204	A4E0A11								4 WITH RETURN A	IR SMOKE DETE	ECTOR							
5	WITH CON	ENIENCE OUTLE	T										6 WITH 2-POSITIO	IN, MOTORIZED	OUTDOOR AIR DA	AMPER						
7	7 WITH HINGED ACCESS PANELS 9 WITH BAS COMPATIBLE THERMOSTAT AND HUMIDITY SENSOR																					
9 WITH BAS COMPATIBLE THERMOSTAT AND HUMIDITY SENSOR																						
11 WITH HOT GAS REHEAT AND DEHUMIDIFICATION CONTROL																						
13 WITH 5 YEAR COMPRESSOR WARRANTY																						
13	MANUFACT	JRED IN THE U	SA										14 WITH LOW-AMBI	ENT CONTROL								
15	WITH FACT	ORY START UP											16 WITH THROUGH	THE BASE ELE	CTRICAL & GAS							
17	WITH BACr	et COMMUNICAT	ION CONTROL	LLER									18 WITH CONDENSA	TE OVERFLOW	SWITCH							
	WITH FILTE											2	20 WITH FACTORY (CONDENSER CO	DIL CORROSION PF	ROTECTION COATING	2					
21	WITH MATC	HED GLOBAL P	LASMA SOLUT	IONS (GPS-IN	MOD) NEEDLE	POINT BI-P	OLAR IONIZATION UNIT	MOUNTED IN CABINET,	UPSTREAM OF COC	LING COIL												
	AIR HANDLER SCHEDULE																					
TAG	MA	KE MOD	EL CF	-M OA	ESP	RPM	HEAT (K	W) V/PH	FAN HP	FAN FLA	FAN LRA	HEATER FL	_A MC	CA	MOCP	LBS NO	DTES					
LE-AHU-	1 DAI)401 40	00 500	1.0	1252	39	460/3	5	6.2	N/A	46.9	66	5.3	70	340 1,2,3,	4,6,8,9,10					
LE-AHU-	2 DAI)401 40	00 500	1.0	1252	39	460/3	5	6.2	N/A	46.9	66	5.3	70	340 1,2,3,	4,6,8,9,10					
MS-AHU-	1 DAI	KIN CAHO18	GDAM 80	00 1200) 1.5	1013	35 (SEPARATE I	FEED) 208/3	7.5	23.3	162.28	97.15 (SEPARATE F	FEED) N/	/A	N/A	1955 1,2,3,5	,6,7,8,9,10					
MS-AHU-	2 DAI	KIN CAHO18	GDAM 80	00 1200) 1.5	1013	35 (SEPARATE I	FEED) 208/3	7.5	23.3	162.28	97.15 (SEPARATE F	FEED) N/	/A	N/A	1955 1,2,3,5	,6,7,8,9,10					
	1 WITH (ONDENSATE OV	ERFLOW SWIT	СН					2 VERTICAL CONFI	GURATION												
	3 WITH 1	HERMAL EXPAN	SION VALVE						4 WITH SINGLE PC	INT ELECTRICAL C	DNNECTION											
	5 WITH S	ECONDARY DRA	IN PAN						6 MOUNT ON NIS	VIBRATION ISOLATI	N											
	7 WITH V	ARREN TECHNO	DLOGY MODEL	CBK, 22.5"X	(16" ELECTRI	C DUCT HEA	ATER		8 WITH MATCHED	GLOBAL PLASMA S	DLUTIONS (GPS-iMC	D) NEEDLEPOINT BI-	-POLAR IONIZATION	UNIT MOUNTED) IN CABINET, UPS	STREAM OF COOLIN	G COIL					
	9 WITH N	IERV 13 FILTER	S					1	0 MANUFACTURED	IN THE USA												
								CONDENSIN	IG UNIT SC	HEDULE]					
TAG		MAKE	MOD	EL	TONNAG	È E	LIQUID	SUCTION	V/PH	FAN F	LA COM	PRESSOR FL	A MCA	MOCP	LBS	NOTES						
LE-CU-		DAIKIN	RCS10H	1200	10		5/8"	1-5/8"	208/3	(2) 3.)	34.8	49.0	80	565	1,2,3,4,5,6,7,8	-					
LE-CU-2	2	DAIKIN	RCS10H	1200	10		5/8"	1-5/8"	208/3	(2) 3.)	34.8	49.0	80	565	1,2,3,4,5,6,7,8	-			1		
MS-CU-	1	DAIKIN	RCS02	20D	20		(2) 5/8"	(2) 1-3/8"	208/3	(2) 4.	2	(2) 37.6	93.6	125	1895	1,2,3,4,5,6,7,8					HOT SIDE	COLD SIDE
MS-CU-	2	DAIKIN	RCS02	20D	20		(2) 5/8"	(2) 1-3/8"	208/3	(2) 4.	2	(2) 37.6	93.6	125	1895	1,2,3,4,5,6,7,8	_	TAG	MAKE	MOI	GPM EWT LWT (FT)	
	1 WITH F	ILTER/DRYER									2 SECURE T	D CONCRETE PAD						HE-1	TACO	PF31-19		
	3 WITH (CONVENIENCE O	JTLET								4 WITH LOW	AMBIENT CONTROL									S STEEL PLATES 2	WITH NBR HT GASKETS
	5 WITH 5	YEAR COMPRE	SSOR WARRA	NTY							6 WITH FACT	ORY CONDENSER CO	IL CORROSION PROT	TECTION COATIN	NG AND HAIL GUAI	RD			3 MANUFACTU	ed in the	UNITED STATES 4	WITH FLANGED CONNECTIONS
	7 MANUF	ACTURED IN TH	E USA								8 WITH FACT	ORY START UP					1					
							PUMI	P SCHEDULE												COOL	ING TOWER SCHEDULE	
	0			MAX	MIN	HE	AD UD		EFF. IN	LET OUT	ET IMPELL				TAG MAK	KE MODEI	_ GPM E	EWT LV	/T WB	V/PH	HP FAN BASIN LENGTH WIDT	H LBS (FT) NOTES
TA	.6	MAKE	MODEL	GPM	GPM	(F	T) HP			N) (IN			S NOTES		CT-1 EVAPO			98 8		480/3	HP FLA (KW) LENGTH WIDT 10 12.4 8 10'-5 1/2" 8'-5 1/2"	
P-	·2	TACO	FI4013D	465	117	13	0 30	1760	75	5 4	11.35	460/3 106	5 1,2,3,4,5			LESS STEEL CONSTRU					ATION LIMIT SWITCH	
	1	SECURE TO N	EW CONCRETE	E PAD AND G	ROUT BASE		I	2 WITH	I ODP MOTOR	1	1	· ·				URED IN THE UNITED					UCTURAL DESIGN FOR IBC COMPLIANCE FOR HIGH WIND/	HURRICANE PRONE REGIONS (159 MPH)
	٦	125 PSI PRES	SURF CLASS					4 WITH	I VFD						5 WITH VARIA	ABLE FREQUENCY DR	IVE AND CONTROL SY	STEM		6 WITH ELE	CTRIC BASIN HEATER	
		MANUFACTURE													7 WITH STAIN	NLESS STEEL BASIN				BWITH 5Y	EAR COMPLETE PRODUCT WARRANTY	
	U														9 WITH INVER	RTER-DUTY TEFC MC	TORS FOR VFD			O WITH NEM	1A 4X STAINLESS STEEL CONTROL PANEL	
															11 WITH EXTER	RNAL SERVICE PLATE	ORM WITH LADDER			2 WITH FAN	MOTOR SPACE HEATERS	
																	R, & DISCONNECT FO	R HEATER		4 WITH EVA		
																OOT LADDER EXTENSI	NC				ER LEVEL CONTROL SYSTEM AND FLOAT VALVE	
															17 WITH FLANG	IGED CONNECTIONS				5 WITH STA	INLESS STEEL INTERNAL SERVICE PLATFORM	

RIAL							_				
D MATE											
© COPYRIGHTED MATERIAL	D E	ß		ß	N		G	R	U		P
	ARC	CHIT	IEC Des	τU	RE	+ [N(GIN	IEEI	RIN	IG
OR APPROV		18 Bilo	xi, P:	Mi 22	ssis 8.3	sip 88	pi 19.	39 250	530)	
3 AUTHORITY	~~ [Dav	vid	J.	M	ac	ha	dc		_	-
HE APPROVING T LAWS.	E	Bi Geri Brai Teri	dfc	y k brd	V. K I A	(ilp . Jo	oat one	ric əs,	k, F Al/	4	
NS THAT MAY HAVE BEEN REQUIRED BY THE APP AND CLAIM ALL RIGHTS OF THE COPYRIGHT LAWS			Ē	555	555 V /	2222 N /	HO	, L L			
HAVE BEEN R - RIGHTS OF		NHO	UN TIM		ENGI	ROF	SS	しいいい	FNDIU		
: THAT MAY H VD CLAIM ALL	ļ	K		r. cil		922 1/					,
RESTRICTIONS NO, PLLC, AN	<u>S</u>			4		172	~~~		2/03	/20	23
NDITIONS OR HADO PATA	VANCLEAVE SCHOOLS HVAC UPGRADES	L	ц Т	•		1	2	î		L C	coc
REY ANY CON	C UPG			C	Ŋ		5 C C	5)]]	•		FI 39
Lans to ver Re copyrigh	HVA		AHY,				5 D D D D D D D D D D D D D D D D D D D		& 12424 HWY 57		
ICINEERED PL HIS SHEET AF	STOO		MEN				7 479		424 H		, MIJ
CONSULT EN	E SCH	L			S E S E S		N ∧		<u>دم</u> م		EAVE
MNER SHALL TES THAT AF	LEAVI						602 H				VANUCLEAVE, MISSISSIPPI 39303
/ AND/OR O' AILS, AND NC	VANC							-			>
DNTRACTOR , AMINGS, DET/	SCAL PROJ	E: I ECT	NO NO:	NE 01	55	.22	.00	8			
ror ∕ subco Is. the dr.	CHEC	KED	Y: BY	JN J	IV IMV	/					
ACI	ဟ										
CONTR OTHER PI											
HESE PLANS. CONTR ERRIDE ANY OTHER PL	CHEDULE:										
DRITY FOR THESE PLANS. CONTR T SHALL OVERRIDE ANY OTHER PL	VAC SCHEDULE										
DVING AUTHORITY FOR THESE PLANS. CONTR ED PLAN SET SHALL OVERRIDE ANY OTHER PL	CAL HVAC SCHEDULE										
) THE APPROVING AUTHORITY FOR THESE PLANS. CONTR D ENGINEERED PLAN SET SHALL OVERRIDE ANY OTHER PL	CHANICAL HVAC SCHEDULE										
UBMITTED TO THE APPROVING AUTHORITY FOR THESE PLANS. CONTR) AND SEALED ENGINEERED PLAN SET SHALL OVERRIDE ANY OTHER PL	MECHANICAL HVAC SCHEDULES										
OCUMENTS SUBMITTED TO THE APPROVING AUTHORITY FOR THESE PLANS. CONTR GNED, DATED AND SEALED ENGINEERED PLAN SET SHALL OVERRIDE ANY OTHER PL		UCTION									
E OFFICIAL DOCUMENTS SUBMITTED TO THE APPROVING AUTHORITY FOR THESE PLANS. CONTR ORIGINAL SIGNED, DATED AND SEALED ENGINEERED PLAN SET SHALL OVERRIDE ANY OTHER PL		JR CONSTRUCTION									
ANS ARE THE OFFICIAL DOCUMENTS SUBMITTED TO THE APPROVING AUTHORITY FOR THESE PLANS. CONTR OCCUR, THE ORIGINAL SIGNED, DATED AND SEALED ENGINEERED PLAN SET SHALL OVERRIDE ANY OTHER PL		ISSUED FOR CONSTRUCTION									
SINEERING PLANS ARE THE OFFICIAL DOCUMENTS SUBMITTED TO THE APPROVING AUTHORITY FOR THESE PLANS. CONTR SCREPANCIES OCCUR, THE ORIGINAL SIGNED, DATED AND SEALED ENGINEERED PLAN SET SHALL OVERRIDE ANY OTHER PL		02.03.2023 ISSUED FOR CONSTRUCTION									
SEALED ENGINEERING PLANS ARE THE OFFICIAL DOCUMENTS SUBMITTED TO THE APPROVING AUTHORITY FOR THESE PLANS. CONTRACTOR / AND/OR OWNER SHALL CONSULT ENGINEERED PLANS TO VERIFY ANY CONDITIONS OR RESTRICTIONS THAT MAY HAVE BEEN REQUIRED BY THE APPROVING AUTHORITY OR APPROVED BY CONDITIONS OR RESTRICTIONS OF THE ORIGINAL SIGNAL SUBMITTED TO THE APPROVING AUTHORITY FOR THESE PLANS. THE DRAWINGS, DETAILS, AND NOTES THAT APPEAR ON THIS SHEET ARE COPYRICHTED BY MACHADO PATANO, PLLC, AND CLAIM ALL RIGHTS OF THE COPYRIGHT LAWS.	REVISION / SUBMITTAL										
DATED AND SEALED ENGINEERING PLANS ARE THE OFFICIAL DOCUMENTS SUBMITTED TO THE APPROVING AUTHORITY FOR THESE PLANS. CONTRA EER OF RECORD. IF DISCREPANCIES OCCUR, THE ORIGINAL SIGNED, DATED AND SEALED ENGINEERED PLAN SET SHALL OVERRIDE ANY OTHER PL	NO. DATE REVISION / SUBMITTAL	REV 0 02.03.2023				F					
	NO. DATE REVISION / SUBMITTAL	02.03.2023	_	_				_			


				RIAL	
LIGHTING SYMBOLS	WIRING SYMBOLS		ONE-LINE SYMBOLS		
CEILING WALL DESCRIPTION	DESCRIPTION		DESCRIPTION		
LED, FLUORESCENT OR H.I.D. LIGHT FIXTURE. LETTER DENOTES FIXTURE TYPE.	WIRING (IN CONDUIT) CONCEALED IN CEILING OR WALL		METER ENCLOSURE	ARCHITECTURE + ENGINEER	
Image: Set Lowinkake Schedule.	WIRING (IN CONDUIT) RUN EXPOSED		METER		F
O O LED OR FLUORESCENT LIGHT FIXTURE. LETTER DENOTES FIXTURE TYPE. SEE LUMINARE SCHEDULE.	WIRING UNDERGROUND (SITE WORK)		CIRCUIT BREAKER	—— Biloxi, Mississippi 39530 ♂ P: 228.388.1950	
Image: Solution of the soluti	TELECOMMUNICATION RACEWAY (SITE WORK)		SWITCH, SINGLE POLE-SINGLE THROW	www.mpdesigngroup.u	- 1
EMERGENCY BATTERY PACK FIXTURE. LETTER DENOTES FIXTURE TYPE. SEE LUMINARE SCHEDULE.	HOMERUN TO PANELBOARD WITH NOMENCLATURE (LETTERS), CIRCUIT NUMBERS (NUMBERS), NUMBER OF CIRCUITS (NUMBER		FUSE	Brad P. Patano, PE کوری Gerrod W. Kilpatrick, PE	E
H.I.D. FLOODLIGHT FIXTURE. LETTER DENOTES FIXTURE TYPE. SEE	L:1,3 OF ARROWS), EACH CIRCUIT TO HAVE GROUND.		FUSE	Bradford A. Jones, AIA 붙 등 문 등 Fernanda A. Silva, AIA	
	ELECTRICAL MANHOLE		FUSED SWITCH	LEY P. PA	
FLOOR WALL CEIL. COUNTR QUAD. DESCRIPTION	T TELECOMMUNICATION MANHOLE		FUSED SWITCH		
	GROUND CONNECTION		DRY TYPE TRANSFORMER	HAK ALL RIGH ALL RIGH	с 3 6 6 5
Image: style="text-align: center;">Image: style="text-align: center;"/>Image: style="text-align: center;"///Image: style="text-align: center;"///Image: style="text-align: center;"//Image: style="text-align: center;"//Image: style="text-align: center;"///Image: style="text-a	\$ SINGLE-POLE TOGGLE SWITCH.	3 6		WIED ON THIS SUC	
	WEATHER PROOF BUTTON SWITCH.	PANEL	PANELBOARD		-
480/277V PANELBOARD	\$ THREE-WAY BUTTON SWITCH.		CURRENT TRANSFORMER	ANY CONDITIONS OR RESTR D BY MACHADO PATANO, P UPGRADES UDDLE, DOG LN,	
208/120V PANELBOARD DISCONNECT SWITCH, AS=FRAME SIZE, AT-FUSE SETTING (NF=NON FUSED), AS/#PNR #P=NUMBER POLES, NR=NEMA ENCLOSURE RATING (NEMA 1 UNLESS	SLIDE DIMMER FLUORESCENT.		POTENTIAL TRANSFORMER	G LN G LN	39565
OTHERWISE NOTED)	\$ _M Switch, motor rated		IGHTING CONTACTOR		
MAGNETIC MOTOR STARTER. SS=STARTER SIZE, NR=NEMA	\$ SWITCH, MOTION SENSOR, LITHONIA WSX SERIES OR APPROVED EQUAL		GROUND FAULT MONITORING	ARY, M BULLI WY 57	SSIP
	PHOTO CELL		KIRK-KEY MECHANICAL INTER-LOCK	INTEREED PLANS TO VERIFY A INTEREED PLANS TO VERIFY A IS SHEET ARE COPYRIGHTED OOLS HVAC I MENTARY, MI H SCHOOLS H SCHOOLS 124 HWY 57 124 HWY 57	ISSI
	OCCUPANCY SENSOR, LITHONIA LIGHTING CEILING MOUNTED 360 OC DEGREE PASSIVE DUAL TECHNOLOGY MOTION SENSOR, OR		GROUND SYSTEM TEST WELL WITH GROUND ROD CONNECTION	CONSULT ENGINEERED PLANS TO VERI APPEAR ON THIS SHEET ARE COPYRICHT APPEAR ON THIS SHEET ARE COPYRICHT RELEMENTARY, N & HIGH SCHOOLS HVAC & HIGH SCHOOLS HVAC & HIGH SCHOOLS ULL 1WY 57, 4725 BULL & 12424 HWY 57	, Ц
MOTOR, THREE-PHASE. HP=DENOTES HORSEPOWER	APPROVED EQUAL		EXOTHERMIC WELD GROUND ROD CONNECTION		М
J J J JUNCTION BOX	GROUNDING CONNECTION BAR	• • E	EXOTHERMIC WELD CONNECTION	OWNER SHALL CO NOTES THAT APPE LOWER 2602 HW 2602 HW	ANCLI
JUNCTION BOX, WALL MOUNTED			4-WAY SF ₆ SWITCH	AND/OR OWNER SHALL CON LS, AND NOTES THAT APPEL AND NOTES THAT APPEL LOWER I 12602 HW	\neq
T			5-WAY SF ₆ SWITCH		
SYSTEM DEVICES	DESCRIPTION			SCALE: NTS PROJECT NO: 0155.22.008 DRAWN BY: DLM	
FLOOR WALL CEIL. DESCRIPTION	SPECIFIC NOTE REFERENCE.		TYPICAL DUAL CIRCUIT AIR BREAK TRANSFORMER DESIGN		
▼ ▼ TELEPHONE OUTLET, FLUSH MOUNTED	1 SFECIFIC NOTE REFERENCE. 100 FEEDER REFERENCE.	400A 4400	TRANSFORMER STATION NUMBER BUILDING NUMBER OR LOCATION		
☑ ▼ ☑ COMBINATION DATA/TELEPHONE OUTLET, FLUSH MOUNTED			LOAD BREAK SF ₆ SWITCH	TERIDE ANY OTHER PLAN	
☑ ☑ CABLE TELEVISION OUTLET, FLUSH MOUNTED	A1E1E21E1E2E1E2E1E2E1E2E1E2E1E2E1E2E1E2E1E2E2E3E3E4E3E4E3E4E3E4E4E4E5E7E4E7E5E7E6E7			L SC	
H FIRE ALARM, COMBINATION AUDIO/VISUAL ANNUNCIATION UNIT. CANDELA AS INDICATED. WALL MOUNTED 7'-6" AFF UNLESS OTHERWISE NOTED, CEILING MOUNTED. MOUNTED.			MOTOR STARTER (NUMBER INDICATES NEMA SIZE)	AUTHORITY FOR THE AUTHORITY FOR THE IN SET SHALL OVER SYMBOL	
S STROBE, WALL MOUNTED 7'-6" AFF UNLESS OTHERWISE NOTED. CEILING MOUNTED CANDELA AS INDICATED.	DESCRIPTION	27	JNDERVOLTAGE RELAY	VIC AUTHO	
P FIRE ALARM PULL STATION. WALL MOUNTED 48" AFF.	SPEAKER. CEILING MOUNT.		VOLT METER		
H HEAT DETECTOR CEILING MOUNTED.	CS INTERCOM CALL STATION.		AMMETER	TED TO THE APPROVING A SEALED ENGINEERED PLA	
SD SMOKE DETECTOR CEILING MOUNTED.	FLOOR MOUNTED MICROPHONE OUTLET ACE BACKSTAGE HALF STAGE POCKET		TRANSIENT VOLTAGE SURGE SUPPRESSION		
DSD DUCT SMOKE DETECTOR, WITH SAMPLING TUBE MOUNTED IN HVAC DUCT.				AL ATION	
FS FLOW SWITCH	WALL MOUNTED VOLUME CONTROL 70 VOLT.				
CM CONTROL MODULE	DC MAGNETIC DOOR CONTACT. SECURITY SYSTEM			E THE OFF THE ORIG	
TS TAMPER SWITCH	GB GLASS BREAK SENSOR. SECURITY SYSTEM MS MOTION DETECTOR SECURITY SYSTEM			PLANS ARI S OCCUR, S OCCUR,	
FAP FIRE ALARM CONTROL PANEL (FACP)				DATE 02.03.2020	
TX TRANSCEIVER	SEC SECURITY SYSTEM PANEL.			NO. NO.	+
ANN FIRE ALARM REMOTE ANNUNCIATOR PANEL.	KP KEYPAD SECURITY SYSTEM.				
VFD VARIABLE FREQUENCY DRIVE	PRO OVERHEAD PROJECTOR			E001	
TBB TELEPHONE BACK BOARD PANEL					
				N 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	
				亡 亡 SCALES ACCORDINGLY	

			KIAL
LIGHTING SYMBOLS	WIRING SYMBOLS	ONE-LINE SYMBOLS	ED MATE
CEILING WALL DESCRIPTION	DESCRIPTION	DESCRIPTION	
LED, FLUORESCENT OR H.I.D. LIGHT FIXTURE. LETTER DENOTES FIXTURE TYPE.	WIRING (IN CONDUIT) CONCEALED IN CEILING OR WALL	METER ENCLOSURE	ARCHITECTURE + ENGINEERING
Image: Set Communication of the source of	WIRING (IN CONDUIT) RUN EXPOSED	M METER	"Designed to Build" 918 Howard Ave Suite F
Image: Description of the section o	WIRING UNDERGROUND (SITE WORK)	CIRCUIT BREAKER	Biloxi, Mississippi 39530EP: 228.388.1950
Image: Constraint of the second state of the second sta	TELECOMMUNICATION RACEWAY (SITE WORK)	SWITCH, SINGLE POLE-SINGLE THROW	David J. Machado, PE
EMERGENCY BATTERY PACK FIXTURE. LETTER DENOTES FIXTURE TYPE. SEE LUMINARE SCHEDULE.	HOMERUN TO PANELBOARD WITH NOMENCLATURE (LETTERS), CIRCUIT NUMBERS (NUMBERS), NUMBER OF CIRCUITS (NUMBER		Brad P. Patano, PE Gerrod W. Kilpatrick, PE
H.I.D. FLOODLIGHT FIXTURE. LETTER DENOTES FIXTURE TYPE. LUMINARE SCHEDULE.	L:1,3 OF ARROWS), EACH CIRCUIT TO HAVE GROUND.	- FUSE	· Bradford A. Jones, AIA 말 : · · 알 Fernanda A. Silva, AIA
	E ELECTRICAL MANHOLE	FUSED SWITCH	N REQUIRED B
FLOOR WALL CEIL. COUNTR QUAD. DESCRIPTION	TELECOMMUNICATION MANHOLE	- FUSED SWITCH	HE HORE PROFESSION
DUPLEX OUTLET; GFCI=GFCI PROTECTION, WP=WEATHER PROOF	GROUND CONNECTION	3 E DRY TYPE TRANSFORMER	ALL RIG
\blacksquare	\$ SINGLE-POLE TOGGLE SWITCH.	3 &	AND CLAIM AND CLAIM AND CLAIM AND CLAIM AND CLAIM AND CLAIM AND AND CLAIM AND
	WEATHER PROOF BUTTON SWITCH.	PANEL PANELBOARD	
480/277V PANELBOARD	\$ THREE-WAY BUTTON SWITCH.	Image: Current transformer	ANY CONDITIONS OR RESTRICTIONS OR RESTRICTIONS OR READES UPGRADES IDDLE, DOG LN, 1 39565
DISCONNECT SWITCH, AS=FRAME SIZE, AT-FUSE SETTING (NF=NON FUSED), #P=NUMBER POLES, NR=NEMA ENCLOSURE RATING (NEMA 1 UNLESS	\$_D SLIDE DIMMER FLUORESCENT.	POTENTIAL TRANSFORMER	C UPGRA MIDDLE, S PI 39565
OTHERWISE NOTED)	\$ _M Switch, motor rated	LIGHTING CONTACTOR	
MAGNETIC MOTOR STARTER. SS=STARTER SIZE, NR=NEMA	\$ SWITCH, MOTION SENSOR, LITHONIA WSX SERIES OR APPROVED EQUAL	GFM GROUND FAULT MONITORING	ARY, M ARY, M ARY, M HVAC BULLI BULLI WY 57 ISSIPP
	PC PHOTO CELL	KIRK-KEY MECHANICAL INTER-LOCK	IN COLS HVAC I SHEET ARE COPYRIGHTED I OOLS HVAC I MENTARY, MI H SCHOOLS 1, 4725 BULLD 124 HWY 57 MISSISSIPPI MISSISSIPPI
	OCCUPANCY SENSOR, LITHONIA LIGHTING CEILING MOUNTED 360 DEGREE PASSIVE DUAL TECHNOLOGY MOTION SENSOR, OR APPROVED EQUAL	GROUND SYSTEM TEST WELL WITH GROUND ROD CONNECTION	
	CONDUIT STUBBED OUT	EXOTHERMIC WELD GROUND ROD CONNECTION	VE SC VE SC VE SC APPEAR C & H HWY HWY SLEAV
	GROUNDING CONNECTION BAR	EXOTHERMIC WELD CONNECTION	AND/OR OWNER SHALL CO ALLS, AND NOTES THAT APPE VANCLEAVE 8 12602 HW VANCLE
		4-WAY SF ₆ SWITCH	LC LC
T		$\begin{bmatrix} 2 \\ 2 \\ 2 \\ 2 \\ 2 \\ 2 \\ 2 \\ 2 \\ 2 \\ 2 $	SCALE: NTS
SYSTEM DEVICES	REFERENCE SYMBOLS DESCRIPTION	TYPICAL DUAL CIRCUIT AIR BREAK TRANSFORMER DESIGN	PROJECT NO: 0155.22.008
FLOOR WALL CEIL. DESCRIPTION	SPECIFIC NOTE REFERENCE.		CHECKED BY: KDB
▼ ▼ TELEPHONE OUTLET, FLUSH MOUNTED	100 FEEDER REFERENCE.	400A 4400 TRANSFORMER STATION NUMBER BUILDING NUMBER OR LOCATION	
Image: Strain of the state	A 1 DETAIL/SECTION REFERENCE: "1" DENOTES DETAIL "A" DENOTES SECTION	LOAD BREAK SF ₆ SWITCH	HESE PLANS. CONTRACT ERRIDE ANY OTHER PLAN SCHEDULE
Image: Second state Image: Second state<	E1 E2 E1 E2 E2 DENOTES DRAWING NUMBER WHERE DETAIL/SECTION IS DRAWN		OL SC
H H FIRE ALARM, COMBINATION AUDIO/VISUAL ANNUNCIATION UNIT. CANDELA AS INDICATED. WALL MOUNTED 7'-6" AFF UNLESS OTHERWISE NOTED, CEILING MOUNTED.	SPECIAL SYSTEMS	MOTOR STARTER (NUMBER INDICATES NEMA SIZE)	AUTHORITY FOR THE IN SET SHALL OVER SYMBOL
S STROBE, WALL MOUNTED 7'-6" AFF UNLESS OTHERWISE NOTED. CEILING MOUNTED CANDELA AS INDICATED.	DESCRIPTION	(27) UNDERVOLTAGE RELAY	
P FIRE ALARM PULL STATION. WALL MOUNTED 48" AFF.	SPEAKER. CEILING MOUNT.	V VOLT METER	ELECTRICAL
H HEAT DETECTOR CEILING MOUNTED.	CS INTERCOM CALL STATION.	A AMMETER	
SD SMOKE DETECTOR CEILING MOUNTED.	Image: MC Floor mounted microphone outlet ace backstage half stage pocket or equal.	TVSS TRANSIENT VOLTAGE SURGE SUPPRESSION	s submit
DSD DUCT SMOKE DETECTOR, WITH SAMPLING TUBE MOUNTED IN HVAC DUCT.	S _V WALL MOUNTED VOLUME CONTROL 70 VOLT.		DOCUMENT IGNED, DA
FS FLOW SWITCH	DC MAGNETIC DOOR CONTACT. SECURITY SYSTEM		SFICIAL B SUBMIT
CM CONTROL MODULE			RE THE C R, THE OI SUIED FOR
TS TAMPER SWITCH			E RE
FAP FIRE ALARM CONTROL PANEL (FACP)			SCREPANG DAT 02.03.2(
TX TRANSCEIVER			REV 0
ANN FIRE ALARM REMOTE ANNUNCIATOR PANEL.			
VFD VARIABLE FREQUENCY DRIVE	OVERHEAD PROJECTOR		E001
TBB TELEPHONE BACK BOARD PANEL			VERIFY SCALES BAR IS ONE INCH ON ORIGINAL DRAWING
			BAR IS ONE INCH ON ORIGINAL DRAWING BAR IS ONE INCH ON ORIGINAL DRAWING BY BY IF NOT ONE INCH ON THIS SHEET, ADJUST SCALES ACCORDINGLY

SYSTEM DEVICES	
FLOOR WALL CEIL. DESCRIPTION	
TELEPHONE OUTLET, FLUSH MOUNTED	
COMBINATION DATA/TELEPHONE OUTLET, FL	JSH MOUNTED
CABLE TELEVISION OUTLET, FLUSH MOUNTED)
H H H H H H H H H H H H H H H H H H H	NNUNCIATION UNIT. CANDE LESS OTHERWISE NOTED,
S STROBE, WALL MOUNTED 7'-6" AFF UNLES MOUNTED CANDELA AS INDICATED.	S OTHERWISE NOTED. CE
P FIRE ALARM PULL STATION. WALL MOUNTED	48" AFF.
H HEAT DETECTOR CEILING MOUNTED.	
SD SMOKE DETECTOR CEILING MOUNTED.	
DSD DUCT SMOKE DETECTOR, WITH SAMPLING TU	JBE MOUNTED IN HVAC D
FS FLOW SWITCH	
CM CONTROL MODULE	
TS TAMPER SWITCH	
FAP FIRE ALARM CONTROL PANEL (FACP)	
TX TRANSCEIVER	
ANN FIRE ALARM REMOTE ANNUNCIATOR PANEL.	
VFD VARIABLE FREQUENCY DRIVE	
TBB TELEPHONE BACK BOARD PANEL	

	REFERENCE SYMBOLS
	DESCRIPTION
	SPECIFIC NOTE REFERENCE.
100	FEEDER REFERENCE.
A 1 E1 E2 E1 E2	DETAIL/SECTION REFERENCE: "1" DENOTES DETAIL "A" DENOTES SECTION "E1" DENOTES DRAWING NUMBER WHERE DETAIL/SECTION IS TAKEN "E2" DENOTES DRAWING NUMBER WHERE DETAIL/SECTION IS DRAWN

SPECIAL SYSTEMS					
	DESCRIPTION				
ISP	SPEAKER. CEILING MOUNT.				
CS	INTERCOM CALL STATION.				
MC	FLOOR MOUNTED MICROPHONE OUTLET ACE BACKSTAGE HALF STAGE POCKET OR EQUAL.				
Sv	WALL MOUNTED VOLUME CONTROL 70 VOLT.				
DC	MAGNETIC DOOR CONTACT. SECURITY SYSTEM				
GB	GLASS BREAK SENSOR. SECURITY SYSTEM				
MS	MOTION DETECTOR. SECURITY SYSTEM.				
SEC	SECURITY SYSTEM PANEL.				
KP	KEYPAD SECURITY SYSTEM.				
PRO	OVERHEAD PROJECTOR				



DEMOLITION NOTES

PLANS DO NOT ATTEMPT TO SHOW ALL DEMOLITION ITEMS. SOME LIGHT FIXTURES, SWITCHES/DIMMERS, EXIT LIGHTS, RECEPTACLES, TELEPHONE, DATA, MISC. OUTLETS, COMMUNICATION DEVICES (FIRE ALARM, PAGING/INTERCOM, NURSE CALL, SECURITY,... ETC.) ARE SHOWN FOR INFORMATION PURPOSES AND GENERAL LAYOUT IN THESE AREAS TO BE RENOVATED. HOWEVER, THE ITEMS SHOWN ARE NOT NECESSARILY COMPLETE, ELECTRICAL CONTRACTOR (E.C.) TO FIELD VERIFY ALL DEMOLITION ITEMS AND PROVIDE REMOVAL OF ALL DEVICES ACCORDINGLY. SEE RELATED NOTES ON MAINTAINING SERVICE TO NON-DEMOLITION AREAS.

E.C. SHALL REMOVE ALL EXISTING LIGHT FIXTURES, SWITCHES/DIMMERS, EXIT LIGHTS, RECEPTACLES, TELEPHONE, DATA, MISC. OUTLETS, WIRING TROUGHS, DUCTS, FILM ILLUMINATORS, COMMUNICATION DEVICES (FIRE ALARM, PAGING/INTERCOM, SECURITY,... ETC.) IN DEMOLITION AREAS. REMOVE CONDUIT/WIRE BACK TO PANEL(S) UNLESS RE-USED FOR NEW AND/OR RELOCATED WORKS. EXISTING RACEWAYS, CONDUITS AND CABLE DUCTS WITH ADEQUATE CAPACITY FOR NEW AND/OR EXISTING LOADS MAY BE RE-USED. SIMILARLY FOR COMMUNICATION SYSTEM CONDUIT/WIRE (REMOVE BACK TO CONTROL PANEL(S) IF NOT RE-USED). FIXTURES NOT INDICATED FOR RE-USE SHALL BE DELIVERED TO A LOCATION TO BE

SPECIFIED BY OWNER. ALL FIXTURES UPSTREAM OR DOWNSTREAM OF DEMOLISHED FIXTURES AND ON THE SAME CIRCUITS SHALL BE RECONNECTED TO MAINTAIN SERVICE, PROVIDE NEW

3. DAMAGE TO EXISTING MATERIALS/EQUIPMENT WILL BE REPAIRED AT NO ADDITIONAL COST TO OWNER. RE-SUPPORT ANY REMAINING CONDUIT OR DEVICE THAT WERE SUPPORTED BY

4. NON-DEMOLITION AREAS: DEMOLITION WORKS SHALL NOT AFFECT AREAS NOT INCLUDED IN DEMOLITION. E.C. SHALL BE RESPONSIBLE FOR THE CONTINUITY OF ALL SERVICES (POWER, TELEPHONE, FIRE ALARM, DATA, PAGING, INTERCOM, ETC.) IN NON-DEMOLITION AREAS. ALL SERVICES SHALL BE MAINTAINED AT ALL TIMES. E.C. SHALL MAINTAIN SERVICE BY EXTENDING, RE-ROUTING AND/OR RECONNECTING ANY CIRCUITS AFFECTED BY DEMOLITION.

E.C SHALL FIELD INVESTIGATE EXISTING ELECTRICAL INSTALLATION. ALL EXISTING INSTALLATION IN THE RENOVATION AREAS THAT ARE TO REMAIN BUT ARE NOT CURRENTLY IN COMPLIANCE WITH CURRENT CODES SHALL BE CORRECTED BY E.C., INCLUDING BUT NOT LIMITED TO THE

UN-SUPPORTED CONDUIT AND JUNCTION BOXES LAYING ON TOP OF CEILING TILES, CONDUIT AND/OR JUNCTION BOXES SUPPORTED ONLY BY TIE-WIRE - RAISE AND SUPPORT CONDUIT WITH STRAP PER SPECS. PROVIDE NEW CONDUIT/WIRE AS REQUIRED.

CIRCUITS WITHOUT A SEPARATE GREEN GROUNDING WIRE - INSTALL A GREEN GROUNDING WIRE FOR EVERY RECEPTACLE OUTLET AND DEVICES. INSTALLATION OF THE GREEN GROUNDING WIRE MAY REQUIRE THE REMOVAL AND RE-INSTALLATION OF THE EXISTING WIRES. PROVIDE NEW WIRE

FIXTURES IMPROPERLY SUPPORTED OR INADEQUATELY SUPPORTED BY DEVICE BOXES - PROVIDE

EMERGENCY AND NORMAL POWER CIRCUITS IN THE SAME CONDUIT - PROVIDE SEPARATION OF

6. ALL EXISTING ABANDONED AND/OR UN-USED CONDUIT/WIRE, SWITCHES/STARTERS, JUNCTION BOXES, COMMUNICATION SYSTEM AND DEVICES IN PROJECT AREAS SHALL BE REMOVED BACK TO PANELS AND/OR CONTROL PANELS. ALL ITEMS DEMOLISHED BY E.C. SHALL BE REMOVED BACK

7. SEE ARCHITECTURAL DRAWINGS FOR ADDITIONAL SCOPE OF DEMOLITION WORK.

8. ALL WORK SHALL BE DONE IN TOTAL COORDINATION WITH THE BUILDING ELECTRICAL MAINTENANCE STAFF TO AVOID ANY INTERRUPTION TO EXISTING CIRCUITS IN USE.

10. CONTRACTOR TO PROVIDE OSHA APPROVED TEMPORARY LIGHTING AND POWER AS REQUIRED FOR


IESIGN GROUI "Designed to Build" 918 Howard Ave Suite F Biloxi, Mississippi 39530 P: 228.388.1950 www.mpdesigngroup.us David J. Machado, PE Brad P. Patano, PE Gerrod W. Kilpatrick, PE Bradford A. Jones, AIA Fernanda A. Silva, AIA A LEY P. PA ENGINEER 2/3/23 17411 S OF MISS """ S Ш UPGRADE Ľ MIDDLE, С 39 Õ \Box Ē HVAC 725 BULLI HWY 57 ISSISSIPP ELEMENTARY, I & HIGH SCHOOL S SCHOOL (24 | MIS 24, E. 1 57 & 1 A< НWY 8 ш EAVE OWER ANCL 2602 CL >AN SCALE: NTS PROJECT NO: 0155,22,008 DRAWN BY: DLM CKFD BY: KDB Ċ ш E002 VERIFY SCALES BAR IS ONE INCH ON ORIGINAL DRAWING NOT ONE INCH ON THIS SHEET, ADJUS SCALES ACCORDINGLY

ABBREVIATIONS									
	А		E		К		Р		U
A AC A/C AF AFF AFG AIC ALUM	AMPERE(S) ALTERNATING CURRENT AIR CONDITIONING AMPERE FRAME ABOVE FINISHED FLOOR ABOVE FINISHED GRADE AMPERES INTERRUPTING CAPACITY ALUMINUM	E.C. EEB EL EM ESD EWC EXIST	ELECTRICAL CONTRACTOR ELECTRICAL EQUIPMENT BUILDING EXHAUST FAN ELEVATION EMERGENCY EMERGENCY SHUTDOWN ELECTRIC WATER COOLER EXISTING	KCMIL KV KVA KW LBS. LEV LTG.	THOUSAND CIRCULAR MILS KILOVOLT KILOVOLT.AMPERES KILOWATT L POUNDS LEVEL LIGHTING	ø PNL PR PE PRI PIR PT PVC	PHASE PANEL PAIR PHOTO ELECTRIC PRIMARY PASSIVE INFRARED POTENTIAL TRANSFORMER POLYVINYL CHLORIDE	UG UL V VAC VDC	UNDERGROUND UNDERWRITER'S LABORATORIES V VOLTS VOLTAGE, ALTERNATING CURREN VOLTAGE, DIRECT CURRENT
AT AWG AHU	AMPERE TRIP AMERICAN WIRE GAGE AIR HANDLING UNIT	FC FF	F FOOT CANDLE FINISHED FLOOR	LV LV	LOW VOLTAGE	PWR	power R	W	W WATTS, WIRE, WIDTH
C CB	C CONDUIT CIRCUIT BREAKER	FLA FL FREQ. FT.	FULL LOAD AMPS FLUORESCENT FREQUENCY FOOT; FEET	MCB MISC MLO MTD MH	MAIN CIRCUIT BREAKER MISCELLANEOUS MAIN LUGS ONLY MOUNTED MOUNTING HEIGHT	REC REQ'D. RGS RM RT	RECEPTACLE REQUIRED RIGID GALVANIZED STEEL ROOM RAINTIGHT	WP XFMR	WEATHERPROOF X TRANSFORMER
CKT CL	CIRCUIT CLASS	C	G	ΜΗ	N	K I	S	XEMK	TRANSFORMER
COND CT CU COMM CWP	CONDUCTOR(S) CURRENT TRANSFORMER COPPER COMMUNICATION CHILLED WATER PUMP	G GALV GFI GND	GROUND GALVANIZED GROUND FAULT INTERRUPTER GROUND H	N NEC N.C. N.O. NF	NEUTRAL NATIONAL ELECTRICAL CODE NORMALLY CLOSED NORMALLY OPEN NONFUSED	SEC SMK SPC SR SS	SECONDARY SMOKE SINGLE POINT CONNECTION SUNRISE SUNSET		
DC	D DIRECT CURRENT	HP HPS HV HZ	HORSEPOWER HIGH PRESSURE SODIUM HIGH VOLTAGE HERTZ	NT NFPA NL NTS	NATIONAL FIRE PROTECTION ASSOCIATION UN SWITCHED NIGHT LIGHT NOT TO SCALE		SUNSET STANDARD SUPERVISORY SWITCHBOARD		
DET.	DETECTOR	JB	JUNCTION BOX	OC OL	O ON CENTER OVERLOAD CONTACT	TYP	T TYPICAL		

I LEDER OUTEDOLL	
YPE THHN/THWN INSUL. COPPER CONDUCTOR AMPACITY BASED ON (75° TEMP. RATING) IN RIGID METAL CONDUIT	
DRY INTERIÓR LOCATIONS: EMT WITH CAST COMPRESSION FITTINGS	
VET EXTERIOR LOCATIONS: RGS WITH CAST FITTINGS	
INDERGROUND INSTALLATIONS: SCHEDULE 80 PVC	

				FEED	DER SCHEDULE			
DRY INTER WET EXTE UNDERGR	RIOR LOCATION	L. COPPER CONDUCTOR AMPACITY BASED IS: EMT WITH CAST COMPRESSION FITTING NS: RGS WITH CAST FITTINGS ATIONS: SCHEDULE 80 PVC APACITIES	ON (75° TEMF S	P. RATING) I	N RIGID METAL CONDUIT			
	3PH+G PHASE + GND. CONDUCTORS AND CONDUIT SIZE		FEEDER DESIGNATION		3PH+N+G PHASE + NEUTRAL + GND. CONDUCTORS AND CONDUIT SIZE	FEEDER DESIGNATION		2 WIRE + GND. OR 1 WIRE + NEUTRAL + GND. CONDUCTORS AND CONDUIT SIZE
20	3#12+#1	2 GND., 3/4"C	(20N)	4#12+#	12 GND., 3/4"C	(20S)	2#12+#	12 GND., 3/4"C
30		0 GND., 3/4"C	(30N)	4#10+#	10 GND., 3/4"C	(30S)	2#10+#	10 GND., 3/4"C
50		GND., 1"C	(50N)		0 GND., 1"C	<u>50S</u>		0 GND., 1"C
(65)		GND., 1"C	(65N)	4#6+#8	GND., 1 1/4"C	(65S)	2#6+#8	GND., 1"C
85		GND., 1 1/4"C	(85N)		GND., 1 1/4"C	<u>(85S)</u>		GND., 1 1/4"C
		GND., 1 1/4"C	(100N)		GND., 1 1/2"C	(1005)		GND., 1 1/4"C
(115)	3#2+#6	GND., 1 1/2"C	(115N)	4#2+#6	GND., 1 1/2"C	(1155)	2#2+#6	GND., 1 1/2"C
(130)	3#1+#6	GND., 1 1/2"C	(130N)	4#1+#6	GND., 2"C	(130S)	2#1+#6	GND., 1 1/2"C
(150)	3#1/0+#	6 GND., 2"C	(150N)	4#1/0+	#6 GND., 2"C	(150S)	2#1/0+	#6 GND., 2"C
(175)	3#2/0+#	6 GND., 2"C	(175N)	4#2/0+	#6 GND., 2 1/2"C	(175S)	2#2/0+	#6 GND., 2"C
200	3#3/0+#	6 GND., 2"C	(200N)	4#3/0+	#6 GND., 2 1/2"C	(200S)	2#3/0+	#6 GND., 2"C
230	3#4/0+#	4 GND., 2 1/2"C	(230N)	4#4/0+	#4 GND., 3"C	(230S)	2#4/0+	#4 GND., 2 1/2"C
255	3#250+#	4 GND., 2 1/2"C	(255N)	4#250+	#4 GND., 3"C	(255S)	2#250+	#4 GND., 2 1/2"C
285	3#300+#	4 GND., 3"C	(285N)	4#300+	#4 GND., 3"C	(285S)	2#300+	#4 GND., 3"C
310	3#350+#	3 GND., 3"C	(310N)	4#350+	#3 GND., 4"C	(310S)	2#350+	#3 GND., 3"C
335	3#400+#	3 GND., 3"C	(335N)	4#400+	#3 GND., 4"C	(335S)	2#400+	#3 GND., 4"C
380	3#500+#	3 GND., 4"C	(380N)	4#500+	#3 GND., 4"C	(380S)	2#500+	#3 GND., 4"C
400	2 SETS(3	#3/0+#3 GND., 2"C)	(400N)	2 SETS(4#3/0+#3 GND., 2 1/2"C)			
420	3#600+#	2 GND., 4"C	(420N)	4#600+	#2 GND., 4"C			
460	2 SETS(3	#4/0+#2 GND., 2"C)	(460N)	2 SETS(4#4/0+#2 GND., 2 1/2"C)			
(510)	2 SETS(3	#250+#1 GND., 2 1/2"C)	(510N)	2 SETS(4#250+#1 GND., 3"C)			
570	2 SETS(3	#300+#4 GND., 2 1/2"C)	(570N)	2 SETS(4#300+#4 GND., 3"C)			
620	2 SETS(3	#350+#1/0 GND., 3"C)	(620N)	2 SETS(4#350+#1/0 GND., 3"C)			
760	2 SETS(3	#500+#1/0 GND., 3"C)	(760N)	2 SETS(4#500+#1/0 GND., 4"C)			
840	2 SETS(3	#600+#2/0 GND., 4"C)	(840N)	2 SETS(4#600+#2/0 GND., 4"C)			
855	3 SETS(3	#300+#2/0 GND., 2 1/2"C)	(855N)	3 SETS(4#300+#2/0 GND., 3"C)			
(1005)	3 SETS(3	#400+#3/0 GND., 3"C)	(1005N)	3 SETS(4#400+#3/0 GND., 3"C)			
(1240)	4 SETS(3	#350+#4/0 GND., 3"C)	(1240N)	4 SETS(4#350+#4/0 GND., 4"C)			
(1650)	5 SETS(3	#400+#250 GND., 3"C)	(1650N)	5 SETS(4#400+#250 GND., 4"C)			
(2010)	6 SETS(3	#400+#350 GND., 3"C)	(2010N)	6 SETS(4#400+#350 GND., 4"C)			
(2660)	7 SETS(3	#500+#450 GND., 4"C)	(2660N)	7 SETS(4#500+#400 GND., 4"C)			
(3040)	8 SETS(3	#500+#500 GND., 4"C)	(3040N)	8 SETS(4#500+#500 GND., 4"C)			
(4180)	11 SETS(3#500+#700 GND., 4"C)	(4180N)	11 SETS	S(4#500+#700 GND., 4"C)			

DESIGN GROUP RCHITECTURE + ENG "Designed to Build" 918 Howard Ave Suite F Biloxi, Mississippi 39530 P: 228.388.1950 www.mpdesigngroup.us David J. Machado, PE Brad P. Patano, PE Gerrod W. Kilpatrick, PE Bradford A. Jones, AIA Fernanda A. Silva, AIA DLEY P. PA ENGINEER 13/23 17411 F OF MISS 111111111 Defails, AID NOTES THAT APPEAR ON THIS SHEET ARE COPYRIGHTED BY MACHADO LA PARADO LA PARAO PARAO LA PARAO PARA SCALE: NTS PROJECT NO: 0155.22.008 DRAWN BY: DLM CHECKED BY: KDB Š ELECTRICAL ABBREVIATIONS FEEDER SCHEDULE 02.03 NO. REV 0 E003 VERIFY SCALES BAR IS ONE INCH ON ORIGINAL DRAWING IF NOT ONE INCH ON THIS SHEET, ADJUST SCALES ACCORDINGLY








Ĩ

DRAWING E004 NOTES


1. CONTRACTOR SHALL COORDINATE WITH OWNER PRIOR TO DISPOSING ALL DEMOLISHED EQUIPMENT.

DRAWING E004 SPECIFIC NOTES

CONTRACTOR SHALL DEMOLISH EXISTING SAFETY SWITCH. CONTRACTOR SHALL DEMOLISH FEEDER BETWEEN SAFETY SWITCH AND HVAC UNIT. CONTRACTOR SHALL DEMOLISH CONDUIT AND FEED BACK TO SORCE. CONTRACTOR SHALL DEMOLISH ALL CONDUIT ABOVE GRADE. CONTRACTOR SHALL ABANDON CONDUIT 6" BELOW GRADE.







DRAWING E005 NOTES

1. CONTRACTOR SHALL COORDINATE WITH OWNER PRIOR TO DISPOSING ALL DEMOLISHED EQUIPMENT.

DRAWING E005 SPECIFIC NOTES

CONTRACTOR SHALL DEMOLISH EXISTING SAFETY SWITCH. CONTRACTOR SHALL DEMOLISH FEEDER BETWEEN SAFETY SWITCH AND HVAC UNIT. CONTRACTOR SHALL DEMOLISH CONDUIT AND FEED FROM SWITCH TO SOURCE. CONTRACTOR SHALL DEMOLISH ALL CONDUIT ABOVE GRADE. CONTRACTOR SHALL ABANDON CONDUIT 6" BELOW GRADE.

				1					
	0.1	0			0	n	•		
	CHITE	CTU	RE	+ [ENC	GIN	IEEI	_	<u> </u>
	18 Ho Biloxi, P:	owo Mi 22	arc issis 8.3	A k ssip 888	ve ppi	Su 39 250	vite 530	C	
_	Davic Bra	l J. d P	М . Р	ac ato	ha	dc c, l), P PE	E	-
	Bradf	ord	ΙA	Ĵ.	one	ÐS,	Al	4	
	8 ⁴	DL ASED	EY	Р. / R0 <i>f</i>	PA;	AN	5		
	Local Street	27	3/	a	R	NAL	10		
		E	DF	MI\$	35\ ••	35			
RADES		Î			Z	ĥ		L	00
C UPGF	MIDDL		'n		Ц С С С	j) 2 1			LI 3950
S HVAC	LARY. I		HOUL		5 B		IWY 57		
HOOL	EMENT				57 479		2424 H		E, MIS
VE SC	/ER EL		R S				ন্ অ		ULEAV
NCLEA	LOW				12602				VAN
SCAL BBOI	E: AS S	SHC	DW	N 22	00	8			
DRAW	IN BY: KED BY	. 01 DLN /: KI	Л Л DB						
PLAN-									
DEMO	DOL								
TRICAL	E SCH								
ELEC									
TAL	UCTION								
JIMBUS / NC	FOR CONSTRI								
ON									
						_)		
BAR		INCH		IOR	lGI				
	NO. DATE REVISION / SUBMITAL ELECTRICAL DEMO PLAN- REVEINANCE AVE SCHOOLS HVAC UPGRADES	NO. DATE REVISION / SUBMITAL ELECTRICAL DEMO PLAN. REV 0 02.03.2023 ISSUED FOR CONSTRUCTION MIDDLE SCHOOL TAN. MDDLE. MIDDLE SCHOOL TAN. TO	ARCHITECTU "Design 918 How Biloxi, Mil P: 22 www.mp David J. Brad P Gerrod V Bradford Fernand ANOCLEAVE SCHOOLS HVAC UPGRADES No David J. Brad P Gerrod V David J. Fernand CHOCLEAVE SCHOOLS HVAC UPGRADES No David J. Brad P Gerrod V David J. Fernand CHOCLEAVE SCHOOLS HVAC UPGRADES No David J. Fernand Chocle Fernand MidDLE SCHOOL Chocle Fernand Chocle Fernand MidDLE SCHOOL Chocle Fernand Chocle Fernand Midd Heroldov Chocle Fernand Chocle Fernand Midd Heroldov	ARCHITECTURE "Designed" "Designed" 918 Howards Biloxi, Missis P: 228.3 WWW.mpde David J. Mi Brad P. P Gerrod W. H Bradford A Fernanda Image: State of the second structure of the s	ARCHITECTURE + E "Designed fr "Designed fr P: 228.388 www.mpdesign David J. Macc Brad P. Pata Gerrod W. Kilp Bradford A. Jo Fernanda A. S Fernanda A. S P: 228.00 Brad P. Pata Gerrod W. Kilp Bradford A. Jo Fernanda A. S Fernanda A.	ARCHITECTURE + ENG "Designed to R 918 Howard Ave Biloxi, Mississippi P: 228.388.19 WWW.mpdesigned Brad P. Patana Gerrod W. Kilpoth Bradford A. Silv PROFORE ENGINEER IT411 OF MISS PROFOR PROFOR PROFORMULAN IT411 OF MISS PROFORMAN PROFO	ARCHITECTURE + ENGIN "Designed to Buil 918 Howard Ave Su Biloxi, Mississippio www.mpdesigngrou David J. Machadac Brad P. Patano, I Gerrod W. Kilpatric Bradford A. Jones, Fernanda A. Silva, PROJECT PROPER IT411 OF MISP PROJECT NO: 0155.22.008 DRINE BCHOOLS DRINE BCHOOLS PROJECT NO: 0155.22.008 DRINE BCHOOLS DRINE BCHOOLS I 12602 HMX 21, 4725 BULLDOOL I 12602 HMX 1260	ARCHITECTURE + ENGINEE "Designed to Build" 918 Howard Ave Suite Biloxi, Mississippi 39533 P: 228.388.1950 WWW.mpdesigngroup. David J. Machado, P. Bradford A. Jones, All Fernanda A. Silva, Al	ARCHITECTURE + ENGINEERIN "Designed to Build" 918 Howard Ave Suite F Biloxi, Mississispi 39530 P: 228.388.1950 WWW.mpdesigngroup.us David J. Machado, PE Brad P. Patano, PE Gerod W. Kilpatrick, PE Bradford A. Jones, AIA Fernanda A. Silva, AIA Fernanda A. Silva












DRAWING E006 NOTES


1. CONTRACTOR SHALL COORDINATE WITH OWNER PRIOR TO DISPOSING ALL DEMOLISHED EQUIPMENT.

DRAWING E006 SPECIFIC NOTES

CONTRACTOR SHALL DEMOLISH EXISTING SAFETY SWITCH. CONTRACTOR SHALL DEMOLISH FEEDER BETWEEN SAFETY SWITCH AND HVAC UNIT. CONTRACTOR SHALL DEMOLISH FEED FROM SOURCE TO SWITCH. CONTRACTOR SHALL DEMOLISH ALL CONDUIT ABOVE GRADE. CONTRACTOR SHALL ABANDON CONDUIT 6" BELOW GRADE.

ALTERNATE 1: CONTRACTOR SHALL DEMOLISH EXISTING PANELBOARD MDP. CONTRACTOR SHALL PRESERVE FEEDER CABLE AND CONDUIT FOR CONNECTION TO NEW PANEL SEE E601 FOR EXISTING PANEL DETAILS. CONTRACTOR SHALL DEMOLISH SERVICE ENTRANCE CONDUCTOR. DEMOLISH SERVICE ENTRANCE CONDUIT AS REQUIRED.






PRINTED: 2/3/2023 1:27 PM BY: Dylan Menhennett LAST SAVED: 2/3/2023 1:22 PM BY: Dmenhennett m:\0155_jackson county school district\0155.22.007_vancleave hvac esser\06-electrical\02-production\01-production drawings\vancleave esser

1.	ALL SAFETY SWITCHE REQUIREMENTS WITH
2.	COORDINATE EXACT ROUGHING IN.
3.	ALL SAFETY SWITCH
4.	ALL SMOKE DUCT D INSTALLED BY THE (FOR TYING INTO THE FOR EXACT QUANTIT
5.	CONTRACTOR SHALL FROM.


DRAWING E151 NOTES

(j


- CHES SHALL BE PROVIDED AND MOUNTED BY THE E.C. COORDINATE EXACT TH THE EQUIPMENT MANUFACTURER.
- WIRING REQUIREMENTS WITH THE MECHANICAL CONTRACTOR PRIOR TO
- CHES SHALL BE HEAVY DUTY. NEMA 1 INDOORS, NEMA 12/3R OUTDOORS.
- DETECTORS AND DAMPER SMOKE DETECTORS SHALL BE PROVIDED AND E CONTROLS CONTRACTOR. FIRE ALARM CONTRACTOR SHALL BE RESPONSIBLE THE FIRE ALARM SYSTEM. CONTRACTOR SHALL REFERENCE MECHANICAL SHEETS TITY AND LOCATIONS.
- . REFERENCE SHEET E613 FOR WHERE TO FEED CONVENIENCE RECEPTACLE







1.	ALL SAFETY SWITCH
	REQUIREMENTS WITH
2.	COORDINATE EXACT ROUGHING IN.
3.	ALL SAFETY SWITCHE
4.	ALL SMOKE DUCT D INSTALLED BY THE (FOR TYING INTO THE FOR EXACT QUANTIT



DRAWING E152 NOTES

Ţ


CHES SHALL BE PROVIDED AND MOUNTED BY THE E.C. COORDINATE EXACT ITH THE EQUIPMENT MANUFACTURER.

T WIRING REQUIREMENTS WITH THE MECHANICAL CONTRACTOR PRIOR TO

THES SHALL BE HEAVY DUTY. NEMA 1 - INDOORS, NEMA 12/3R - OUTDOORS.

T DETECTORS AND DAMPER SMOKE DETECTORS SHALL BE PROVIDED AND IE CONTROLS CONTRACTOR. FIRE ALARM CONTRACTOR SHALL BE RESPONSIBLE THE FIRE ALARM SYSTEM. CONTRACTOR SHALL REFERENCE MECHANICAL SHEETS ITITY AND LOCATIONS.

THE REGISTERED ENGINEER	NEER OF RECORD	D. IF DISCREPANC	ALES OCCUR, THE ORIGINAL SIGNED, DATED	THE REGISTERED ENGINEER OF RECORD. IF DISCREPANCIES OCCUR, THE ORIGINAL SIGNED, DATED AND SEALED ENGINEERED PLAN SET SHALL OVERRIDE ANY OTHER PLANS. THE DRAWINGS, DETAILS, AND NOTES THAT APPEAR ON THIS SHEET ARE COPYRIGHTED BY MACHADO PATANO, PLLO	PLANS. THE DRAWINGS, DETAILS, AND NOTES THAT APPEAR ON THIS SHEET ARE COPYRIGHTED BY MACHADO PATANO, PLLC,	E COPYRIGHTED BY MACHADO PATANO, PLLC, AND CLAIN	AND CLAIM ALL RIGHTS OF THE COPYRIGHT LAWS	, AND CLAIM ALL RIGHTS OF THE COPYRIGHT LAWS.	COPYRIGHTED MATERIAL
		NO. DATE	E BEVISION / SUBMITTAL	MECHANICAL POWER PLAN-	STOOHOS SCHOOLS	HVAC UPGRADES			D E
		REV 0 02.03.2023	023 ISSUED FOR CONSTRUCTION	MIDDLE SCHOOL	E: AS ECT NC WN BY: KED B		YS YOUNG AN	P18 He Biloxi P: vww.r Davic Bra Gerro Bradf	S I Chite
ERIFY INCH OF	E1				& HIGH SCHOOLS DIW COLVER COLV		2/3/	signe oward , Missi : 228.3 mpde d J. M d P. P d W. ord A anda	G N Cture
N ORIGI THIS S	5				222.00 NMV 57 A725		P. P.A ROFES INEER	d Ave ssipp 388.1 sign achc achc atan Kilpa . Jon	•
NAL DF 1" HEET, /	2				8 12424 HW 57		ANO MAN MA	e Suite i 3953 950 group ado, I o, PE trick, es, A	R (
							11111111111111111111111111111111111111	e F 30 D.US PE PE IA	-
-				_				-	PG



DRAWING E153 NOTES

1. ALL SAFETY SWITCHES SHALL BE PROVIDED AND MOUNTED BY THE E.C. COORDINATE EXACT REQUIREMENTS WITH THE EQUIPMENT MANUFACTURER.

2. COORDINATE EXACT WIRING REQUIREMENTS WITH THE MECHANICAL CONTRACTOR PRIOR TO

3. ALL SAFETY SWITCHES SHALL BE HEAVY DUTY. NEMA 1 - INDOORS, NEMA 12/3R - OUTDOORS.

4. ALL SMOKE DUCT DETECTORS AND DAMPER SMOKE DETECTORS SHALL BE PROVIDED AND INSTALLED BY THE CONTROLS CONTRACTOR. FIRE ALARM CONTRACTOR SHALL BE RESPONSIBLE FOR TYING INTO THE FIRE ALARM SYSTEM. CONTRACTOR SHALL REFERENCE MECHANICAL SHEETS FOR EXACT QUANTITY AND LOCATIONS.

5. CONTRACTOR SHALL REPLACE EXISTING MDP WITH NEW MDP AS ALTERNATE #1. CONTRACTOR SHALL PLACE NEW MDP IN EXISTING LOCATION. CONTRACTOR SHALL REFERENCE SHEET E611 FOR

DRAWING E153 SPECIFIC NOTES


ALTERNATE 1: CONTRACTOR SHALL PROVIDE AND INSTALL NEW SWITCHBOARD MDP. CONTRACTOR SHALL CONNECT EXISTING FEEDER CONDUCTOR TO NEW SWITCHBOARD. CONTRACTOR SHALL MODIFY FEEDER CONDUCTOR AND CONDUIT AS REQUIRED. CONTRACTOR SHALL FIELD COORDINATE EXISTING MDP SIZE AND MATCH WITH NEW MDP. SEE SHEET E611 FOR DETAILS.


Ž


- EXISTING TRANSFORMER

DESIGN GROUP RCHITECTURE + EN "Designed to Build" 918 Howard Ave Suite F Biloxi, Mississippi 39530 P: 228.388.1950 www.mpdesigngroup.us David J. Machado, PE Brad P. Patano, PE Gerrod W. Kilpatrick, PE Bradford A. Jones, AIA Fernanda A. Silva, AIA DLEY P. PA ENGINEER 2/3/23 17411 . € OF MISS ******** VANCLEAVE SCHOOLS HVAC UPGRADES HWY 57, 4725 BULLDOG LN, & 12424 HWY 57 LEAVE, MISSISSIPPI 39565 LOWER ELEMENTARY, MIDDLE & HIGH SCHOOLS НWY VANCL 12602 SCALE: AS SHOWN PROJECT NO: 0155.22.008 DRAWN BY: DLM HECKED BY: KDB **POWER PL** N N E153 VERIFY SCALES BAR IS ONE INCH ON ORIGINAL DRAWING F NOT ONE INCH ON THIS SHEET, ADJUST

SCALES ACCORDINGLY









DRAWING E601 SPECIFIC NOTES

CONTRACTOR SHALL DEMOLISH EXISTING SAFETY SWITCH AND CONTROLS, CONTRACTOR SHALL DEMOLISH FEED FROM SOURCE TO DISCONNECT . CONTRACTOR SHALL DEMOLISH FEED FROM DISCONNECT TO EQUIPMENT. CONTRACTOR SHALL DEMOLISH ALL CONDUIT ABOVE GRADE.









DRAWING E602 SPECIFIC NOTES

CONTRACTOR SHALL DEMOLISH EXISTING SAFETY SWITCH AND CONTROLS, CONTRACTOR SHALL DEMOLISH FEED FROM SOURCE TO DISCONNECT. CONTRACTOR SHALL DEMOLISH FEED FROM DEMOLISH FEED FROM SOURCE TO DISCONNECT. CONTRACTOR SHALL DEMOLISH FEED FROM DISCONNECT TO EQUIPMENT. CONTRACTOR SHALL DEMOLISH ALL CONDUIT ABOVE GRADE. CONTRACTOR SHALL ABANDON CONDUIT 6" BELOW GRADE.

THE REGISTER	REGISTERED ENGINEER OF RECORI	RECORD. IF DIS	JISCREPANCIES	OCCUR, THE ORIGINAL SIGNED, DATEL	DIE DISCREPANCIES OCCUR, THE ORIGINAL SIGNED, DATED AND SEALED ENGINEERED PLAN SET SHALL OVERRIDE ANY OTHER PLANS. TH	HE DRAWINGS, E	PLANS. THE DRAWINGS, DETAILS, AND NOTES THAT APPEAR ON THIS SHEET ARE COPYRIGHTED BY MACHADO PATANO, PLLC,	LC, AND CLAIM ALL RIGHTS OF THE COPYRIGHT LAWS	RIGHT LAWS.	COPYRIGHTED MATERIAL
		NO.	DATE	REVISION / SUBMITTAL	ELECTRICAL ONE-LINE DIAGRAM	SCAL PROJ DRAV CHEC	VANCLEAVE SCHOOLS HVAC UPGRADES			D E
		REV 0	02.03.2023	ISSUED FOR CONSTRUCTION	DEMOLITION PLAN- HIGH SHCOOL	E: NTS ECT NC VN BY: KED BY	LOWER ELEMENTARY. MIDDLE.	A VOLUCE C	P18 Ho Biloxi, P: vww.r Davic Brad Gerro Bradfo	S I
	E6): 0155. DLM /: KDB	& HIGH SCHOOLS DTW KDB	DLEY DLEY ENGIN 2/3/2 174 OF	signec oward Missis 228.38 npdes d J. Mc d P. Pc d P. Pc d W. K ord A. inda A	GN
ORIGINA						22.008	12602 HWY 57, 4725 BULLDOG LN,	83 11 NISSIS	to Bu Ave S sippi 3 88.195 signgro achad atano, ilpatri Jones	G F + ENGI
L DRA 1" ET, AC							& 12424 HWY 57		vild" Suite 9530 50 50 0, Pl , PE ck, P 5, Al/	? () Neef
-							VANCLEAVE, MISSISSIPPI 39565		F) US E PE	•••



SCALES ACCORDINGLY



DRAWING E604 NOTES

- 1. CONTRACTOR SHALL COORDINATE WITH OWNER PRIOR TO DISPOSING ALL DEMOLISHED EQUIPMENT.
- 2. CONTRACTOR SHALL FILED VERIFY EXISTING PANEL BOARD SCHEDULE.


19 50A/ 2P HOT W/H SOUTH A/C UNIT S. BÁTHRM HP 3 MEZZANINE 30AMP 2P WALL 50AMP 2P (EX)

DRAWING E604 SPECIFIC NOTES

CONTRACTOR SHALL DEMOLISH EXISTING SAFETY SWITCH AND CONTROLS, CONTRACTOR SHALL DEMOLISH FEED FROM SOURCE TO DISCONNECT. CONTRACTOR SHALL DEMOLISH FEED AND DEMOLISH FEED FROM SOURCE TO DISCONNECT. CONTRACTOR SHALL DEMOLISH FEED AND CONDUIT FROM EQUIPMENT TO DISCONNECT. CONTRACTOR SHALL DEMOLISH ALL CONDUIT ABOVE GRADE. CONTRACTOR SHALL ABANDON CONDUIT 6" BELOW GRADE.


2 CONTRACTOR SHALL NOT DEMOLISH BREAKER.


RIAL											
© COPYRIGHTED MATERIAL				-							
© COPYRIG	D E			••		•	••	0	-	P	
		"D	ECTU esigi How	ne	d t	o E	Buil	d"		G	
		Bilox F	ki, M P: 22 .mp	issis 8.3	ssip 888	pi .19	39 950	53	0		
		Bro	id J. ad P	'. P	ato	ano	o, I	РΕ		-	
COPYRIGHT LAWS.		Brac	od V Iforc and	A k	Ĵ.	one	es,	AL	Ą		
OF THE COPY		۱. ۵۸ ا	2 ADL	EY	P. / ROF	PA;	AN				
ALL RIGHTS OF THE		4	DCEN.	3/	NEE	R	ONAL	_	11111111		
, AND CLAIM			ATE) OF	MI	351 ••	55				
ATANO, PLLC,)ES										
	E B B CHOOLS HVAC UPGRADES		C L L L			Z C	5			6966	
VENTED BY 1	AC UF			רג גר				57		טוררו	
T ARE COPY	LS HV			CHOC		725 BI	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			りつう	
N THIS SHEE	CHOO			5 H2		57 47		& 12424 HWY 57		VANULEAVE, MISSISSIPPI 39303	
AT APPEAR (VE SO			Х Х		AWY		৵		ULEA	
UN NOTES TH	NCLE					12602				VAN	
, DETAILS, AND	IAN SCAL	E: NT	S								
HE DRAWINGS	PROJ DRAV CHEC	ECT N VN BY	10: 0 : DL1 <u>BY:</u> K	155 и <u>D</u> В	.22	.00	8				
R PLANS. T											
JE ANY OTHE	DIAGR/	СЕ									
ALL OVERRID	ELECTRICAL ONE-LINE DIAGRAM	DEMOLITION PLAN- MIDDLE									
PLAN SET SH		N PLA									
ENGINEERED	TRICA	OLITIO									
AND SEALED	ELE(DEM									
NED, DATED	-AL	CTION									
. SIG	LLIM	CONSTRU									
ORIGINAL	I / SUB	Ř		1							
DCCUR, THE ORIGINAL	REVISION / SUBMITTAL	ISSUED FOR CONSTRUCTION									
CREPANCIES OCCUR, THE ORIGINAL	DATE REVISION / SUB										
SEALED ENGINEERING THAN SHE THE OFFICIANT SUBMITED TO THE AFFOUND		REV 0 02.03.2023 ISSUED FOR (
	DATE	REV 0 02.03.2023		6							
THE UNUNAL SUMEL, DATED AND SEALD ENGINEERING FLANS ARE THE OFTICAL THE REGISTERED ENGINEER OF RECORD. IF DISCREPANCIES OCCUR, THE ORIGINAL	NO. DATE	REV 0 02.03.2023		FY	sc	AL	ES				




CONTRACTOR SHALL FIEL CONTRACTOR SHALL MOE
DRA
CONTRACTOR SHALL F SHOWN. CONTRACTOR
CONTRACTOR SHALL L
VFD SHALL BE PROVI COORDINATE REQUIREI
VFD SHALL BE PROVI COORDINATE REQUIREI


DRAWING E610 NOTES












CONTRACTOR SHALL PROVIDE AND INSTALL NEW CIRCUIT BREAKER IN EXISTING PANEL BOARD AS SHOWN. CONTRACTOR SHALL PROVIDE AND INSTALL NEW DISCONNECT.


DRAWING E612 NOTES


1. CONTRACTOR SHALL FIELD COORDINATE EXISTING MOUNTING SPACE FOR EXISTING PANELBOARD. CONTRACTOR SHALL MODIFY EXISTING PANEL BOARD FOR NEW EQUIPMENT.

DRAWING E612 SPECIFIC NOTES

THAT MAY HAVE BEEN REQUIRED BY THE APPROVING AUTHORITY OR APPROVED BY COPYRIGHTED MATERIAL CLAIM ALL RIGHTS OF THE COPYRIGHT LAWS.	ARC 9 	18 Ho Biloxi, P: ww.r	sign Sign Mis 228 mpc J. J. I d P. d W ord	RE + ed 1 rd A sissip 3.388 lesig Mac Pat . Kill A. J a A.	ve opi 3.19 3.19 3.19 3.19 3.19 3.19 3.19 3.19	SIN Suik 39: 50 rot do p, F rick es,	EEF d" ite 530 , Pf 2E <, P	F) US E	PG
		A S ANNOR SA	AT.	PRO IGINEE 3/2 17411 F MI	3 SSI	NO NAL OUN			
THE ORIGINAL SIGNED, DATED AND SEALED ENGINEERING PLANS ARE THE OFFICIAL DOCUMENTS FOR THESE PLANS. CONTRACTOR / SUBGITIED TO VERT ANY CONDITIONS OF RESTRICTIONS OF REST	VANCLEAVE SCHOOLS HVAC UPGRADES	LOWER ELEMENTARY. MIDDLE.			Image: Signal and Sig		& 12424 HWY 5/		
MILLED TO THE APPROVING AUTHORITY FOR THESE PLANS. CONTRACTOR / SUBCOT ND SEALED ENGINEERED PLAN SET SHALL OVERRIDE ANY OTHER PLANS. THE DRAV		PLAN- HIGH SHCOOL	DLM	B					
NS ARE THE OFFICIAL DOCUMENTS SUBN DCCUR, THE ORIGINAL SIGNED, DATED AN	REVISION / SUBMITTAL	02.03.2023 ISSUED FOR CONSTRUCTION							
SEALED ENGINEERING PLA DRD. IF DISCREPANCIES C	NO. DATE	REV 0 02.03.2023							
THE ORIGINAL SIGNED, DATED AND SEAT THE REGISTERED ENGINEER OF RECORD.					AL RIGIN	ES IAL I IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII	DRA "		







2 NOT NEEDED.

DRAWING E614 NOTES

1. CONTRACTOR SHALL FIELD COORDINATE EXISTING MOUNTING SPACE FOR EXISTING PANELBOARD. CONTRACTOR SHALL MODIFY EXISTING PANEL BOARD FOR NEW EQUIPMENT.

DRAWING E614 SPECIFIC NOTES

CONTRACTOR SHALL PROVIDE AND INSTALL NEW CIRCUIT BREAKER IN EXISTING PANEL BOARD AS SHOWN. CONTRACTOR SHALL PROVIDE AND INSTALL NEW DISCONNECT.

© COPYRIGHTED MATERIAL									
	D E	S CHITEC	CTUR	E +	EN(R GIN	IEE	U RIM	P
TY OR APPROVED		18 Ho Biloxi,	wa Mis 228	rd . siss .38	Ave ppi 8.19	SL 39 950	vite 530	C	
: APPROVING AUTHOR LAWS.	C	David Brac Gerroc Bradfo	J. <i>I</i> J. <i>I</i> J.P. d W brd	Ла Ра . Kil А	cha tan pat Jon	dc o, l ric əs,	, P PE k, F Al,	E PE A	-
REQUIRED BY THE F THE COPYRIGHT		Ferna		Y P PRC	Silv PA	a,	Al/	4	
T MAY HAVE BEEN AIM ALL RIGHTS O		S MUCE	SEE EN	IGINE 3/2 1741	3	ONAL	10	+++++++++	
ESTRICTIONS THA- NO, PLLC, AND CL	S	****** ****	EO	FM	1551	55			
CONDITIONS OR F MACHADO PATAI	PGRADE	DLE.			N I C				600A
VS TO VERIFY ANY COPYRIGHTED BY	HVAC U	ARY, MID			BIII DC		VY 57		
' ENGINEERED PLAI N THIS SHEET ARE	STOOH	EMENT/			57 4725		8 12424 HWY 57		E, MISSI
R SHALL CONSULT THAT APPEAR ON	EAVE SC	LOWER ELEMENTARY, MIDDLE.	Х, Н	5	12602 HWV 57 4725 BUILDOG I N		~ð		VANULEAVE, MISSISSIPPI 39303
R / AND/OR OWNE ETAILS, AND NOTES	VANCLEAVE SCHOOLS HVAC UPGRADES								٧A
SUBCONTRACTOR HE DRAWINGS, DE	SCAL PROJ DRAW	E: NTS ECT NO VN BY: I KED BY	: 015 DLM : KD	55.2 В	2.00	8			
CONTRACTOR / OTHER PLANS. T	RAM								
OR THESE PLANS. L OVERRIDE ANY (INE DIAG	HOOL							
ING AUTHORITY FO	AL ONE-L	DLE SCH							
D TO THE APPROV EALED ENGINEERED	ELECTRICAL ONE-LINE DIAGRAM	PLAN- MIDDLE SCHOOL							
UMENTS SUBMITTEI ED, DATED AND SE									
FFICIAL DOCL	REVISION / SUBMITTAL	ISSUED FOR CONSTRUCTION							
는 프 드 는 OF	õ	L H L							
RING PLANS ARE THE O ANCIES OCCUR, THE OF									
Provide the official documents submitted to the approving authority for these plans. Contractor / subcontractor / and/or owner shall consult engineered plans to verify any conditions or restrictions that may have been required by the approving authority or approved by approved by accepancies occur, the original signed, dated and sealed engineered plans. The drawings, details, and notes that appear on this sheet are copyrighted by machado patano, pllc, and claim all rights of the copyright laws.	NO. DATE REVISION	REV 0 02.03.2023 ISSUE							
, DATED AND SEALED ENGINEERING PLANS ARE THE O INEER OF RECORD. IF DISCREPANCIES OCCUR, THE OF		REV 0 02.03.2023)	1				
THE ORIGINAL SIGNED, DATED AND SEALED ENGINEERING PLANS ARE THE O THE REGISTERED ENGINEER OF RECORD. IF DISCREPANCIES OCCUR, THE OF	NO. DATE	REV 0 02.03.2023	RIF	YS	CAL	ES		AWI	NG